

QS(P) series fountain submersible pump

Model	Flow	Head	Power	Current	Max. Dia.	Pump height	Flange Dia	Discharge Dia.
QS Series	m ³ /h	m	KW	A	mm	mm	mm	mm
QS(P)10-10-0.55	10	10	0.55	2.2	150	450	150	50
QS(P)15-7-0.55	15	7	0.55	2.2	150	450	150	50
QS(P)10-14-0.75	10	14	0.75	2.6	150	450	150	50
QS(P)15-10-0.75	15	10	0.75	2.6	150	450	150	50
QS(P)15-14-1.1	15	14	1.1	3.2	156	520	156	50
QS(P)40-6-1.1	40	6	1.1	3.2	156	520	156	80
QS(P)25-9-1.1	25	9	1.1	3.2	156	520	156	65
QS(P)25-12-1.5	25	12	1.5	4.2	156	520	156	65
QS(P)40-9-1.5	40	9	1.5	4.2	156	520	156	80
QS(P)10-40/3-2.2	10	40	2.2	5.7	170	680	150	50
QS(P)15-26-2.2	15	26	2.2	5.7	170	580	150	50
QS(P)20-20-2.2	20	20	2.2	5.7	170	580	150	65
QS(P)25-17-2.2	25	17	2.2	5.7	168	580	150	65
QS(P)40-12-2.2	40	12	2.2	5.7	168	580	150	65
QS(P)65-7-2.2	65	7	2.2	5.7	168	580	150	90
QS(P)15-34/2-3	15	34	3	7	168	650	156	50
QS(P)10-54/3-3	10	54	3	7	170	680	150	50
QS(P)25-25-3	25	25	3	7	170	580	150	65
QS(P)20-30/2-3	20	30	3	7	168	650	156	65
QS(P)40-16-3	40	16	3	7	168	580	168	65
QS(P)50-13-3	50	13	3	7	168	580	168	90
QS(P)80-7-3	80	7	3	7	187	580	168	90
QS(P)65-10-3	65	10	3	7	168	580	168	90
QS(P)100-6-3	100	6	3	7	200	580	168	90
QS(P)100-65/5-4	10	65	4	10.2	168	750	150	50
QS(P)100-72/4-4	10	72	4	10.2	168	720	150	50
QS(P)10-81/6-4	10	81	4	10.2	168	780	150	50
QS(P)15-54/4-4	15	54	4	10.2	168	720	150	50
QS(P)20-40/2-4	20	40	4	10.2	168	730	168	65
QS(P)25-30/2-4	25	30	4	10.2	168	730	168	65
QS(P)30-30/2-4	30	30	4	10.2	168	730	168	65
QS(P)32-26-4	32	26	4	10.2	168	670	168	65
QS(P)40-21-4	40	21	4	10.2	168	630	168	65
QS(P)50-16-4	50	16	4	10.2	168	630	168	90
QS(P)65-13-4	65	13	4	10.2	168	630	168	90
QS(P)65-15-4	65	15	4	10.2	168	630	168	90
QS(P)80-12-4	80	12	4	10.2	187	630	168	90
QS(P)100-9-4	100	9	4	10.2	200	630	168	90

QS(P)100-95/7-5.5	10	95	5.5	13.4	187	1080	168	50
QS(P)10-108/8-5.5	10	108	5.5	13.4	187	1150	168	50
QS(P)15-65/5-5.5	15	65	5.5	13.4	187	960	168	50
QS(P)20-54/3-5.5	20	54	5.5	13.4	187	870	168	65
QS(P)25-40/3-5.5	25	40	5.5	13.4	187	870	168	65
QS(P)30-40/3-5.5	30	40	5.5	13.4	187	780	168	90
QS(P)40-30/2-5.5	40	30	5.5	13.4	187	780	168	90
QS(P)40-28-5.5	40	28	5.5	13.4	187	720	168	90
QS(P)50-26-5.5	50	26	5.5	13.4	187	780	168	90
QS(P)65-20-5.5	65	20	5.5	13.4	187	720	168	90
QS(P)65-18-5.5	65	18	5.5	13.4	187	720	168	90
QS(P)80-15-5.5	80	15	5.5	13.4	187	720	168	90
QS(P)100-12-5.5	100	12	5.5	13.4	200	720	200	125
QS(P)120-10-5.5	120	10	5.5	13.4	200	720	200	125
QS(P)220-5-5.5	220	5	5.5	13.4	200	720	200	150
QS(P)10-121/9-7.5	10	121	7.5	18.6	187	1250	168	50
QS(P)15-80/6-7.5	15	80	7.5	18.6	187	1200	168	50
QS(P)20-65/5-7.5	20	65	7.5	18.6	187	960	168	65
QS(P)20-75/4-7.5	20	75	7.5	18.6	187	1130	168	65
QS(P)25-65/5-7.5	25	65	7.5	18.6	187	960	168	65
QS(P)30-50/3-7.5	30	50	7.5	18.6	187	950	168	65
QS(P)30-54/3-7.5	30	54	7.5	18.6	187	950	168	65
QS(P)32-48/4-7.5	32	48	7.5	18.6	187	950	168	65
QS(P)40-40/2-7.5	40	40	7.5	18.6	187	820	168	90
QS(P)50-30/2-7.5	50	36	7.5	18.6	187	950	168	90
QS(P)50-36/3-7.5	50	36	7.5	18.6	187	950	168	90
QS(P)65-25-7.5	65	25	7.5	18.6	187	740	168	90
QS(P)80-22/2-7.5	80	22	7.5	18.6	187	820	168	90
QS(P)100-15-7.5	100	15	7.5	18.6	200	740	200	125
QS(P)100-17-7.5	100	17	7.5	18.6	200	740	200	125
QS(P)250-8-7.5	250	8	7.5	18.6	200	740	200	150