

型号Model		NF200DGM	NF250DGM	NF300DGM
参数 Technical Date		NF200SGM	NF250SGM	NF300SGM
名义制冷量 Nominal Capacity (kW)		3.76	4.12	5.48
匹数 Horse Power (HP)		2	2.5	3
压缩机 Compressor		ZB15	ZB19	ZB21
风机个数 Fan Quantity		1	1	1
风叶直径 Fan Diameter (mm)				
风量 Air Flow (m <sup>3</sup> /h)		6300	6300	6300
风机功率 Fan Motor Power (W)		≤170	≤170	≤170
连接管管径 Connection Pipe Diameter	液管 Liquid Line (inch)	3/8	3/8	3/8
	气管 Gas Line (inch)	3/4	3/4	3/4
电源 Power Souch		220V/1/50Hz	220V/1/50Hz	220V/1/50Hz
		380V/3/50Hz	380V/3/50Hz	380V/3/50Hz
额定电流 Rated Current (A)		12.2/5.1	13.7/5.1	17.2/6.5
外形尺寸External Dimensions	宽 Width (mm)	1050	1050	1050
	高 Height (mm)	845	845	845
	深 Deep (mm)	430	430	430
净重 Net Weight (kg)		65	68	78

注：制冷剂R404A，环境温度32℃，蒸发温度-10℃，吸气温度20℃。

Remark:R404A refrigerant,Duty at 32℃ ambient temperature,-10℃ Evaporating

NF350DGM NF350SGM	NF400DGM NF400SGM	NF500SGM	NF600SGM	NF700SGM	NF800SGM
6.02	6.82	8.67	10.15	11.17	13.38
3.5	4	5	6	7	8
ZB26	ZB29	ZB38	ZB45	ZB48	ZB58
1	1	2	2	2	2
490					
6300	6300	10800	10800	10800	10800
≤170	≤170	≤340	≤340	≤340	≤340
1/2	1/2	1/2	1/2	1/2	5/8
3/4	3/4	7/8	7/8	7/8	7/8
220V/1/50Hz	220V/1/50Hz	380V/3/50Hz	380V/3/50Hz	380V/3/50Hz	380V/3/50Hz
380V/3/50Hz	380V/3/50Hz				
17.9/7.9	20.1/8.7	11.5	13.0	13.6	17.9
1050	1050	1050	1050	1050	1200
845	845	1245	1245	1245	1245
430	430	430	430	430	580
91	96	106	119	123	147

temperature, 20°C suction temperature