

## LFJX系列吸顶式冷风机

### LFJX series ceiling type air cooler

库温Room temp.  $\geq -2^{\circ}\text{C}$ , 片距Fin spacing 3.5mm R404A

配丹佛斯膨胀阀(默认 $T_c=0^{\circ}\text{C}/7\text{KTD}$ ) With Danfoss expansion valve(default  $T_c=0^{\circ}\text{C}/7\text{KTD}$ )

#### 技术数据 Technical Data

型号 Model	制冷量 Capacity(W)	面积 Surface	管容 Tube volume	接口尺寸(inch) Connection Dimension		外形尺寸(mm) External Dimension			安装尺寸(mm) Installation Dimension	
	$T_c=0^{\circ}\text{C}/7\text{KTD}$	$\text{m}^2$	$\text{dm}^3$	进口Inlet	出口Outlet	L	W	H	A	B
LFJX3.3/0.65M	650	3.3	0.85	3/8	5/8	530	545	210	497	525
LFJX4.0/0.75M	750	4	1.02	3/8	5/8	530	545	210	497	525
LFJX5.2/0.95M	950	5.2	1.32	3/8	5/8	650	545	210	617	525
LFJX6.3/1.25M	1250	6.3	1.55	3/8	5/8	870	545	210	837	525
LFJX7.6/1.5M	1500	7.6	1.86	3/8	5/8	870	545	210	837	525
LFJX9.7/1.9M	1900	9.7	2.33	3/8	5/8	1250	545	210	1217	525
LFJX12/2.3M	2300	12	2.8	3/8	5/8	1250	545	210	1217	525
LFJX16/3.0M	3000	16	3.75	3/8	5/8	1250	545	260	1217	525

型号 Model	风机 Fan						电化霜 Defrost Heater 水盘Drain Pan	膨胀阀 Expansion Valve	阀芯 Orifice
	数量(台) Quality	直径(mm) Diameter	风量( $\text{m}^3/\text{h}$ ) Airflow	射程(m) Air Throw	输入功率(W) Input Power	电源 Voltage:50/60Hz			
LFJX3.3/0.65M	1	230	700	3.5	10	220-240V	580W	TES2	0#
LFJX4.0/0.75M	1	230	700	3.5	10	220-240V	580W	TES2	1#
LFJX5.2/0.95M	1	230	700	3.5	10	220-240V	760W	TES2	1#
LFJX6.3/1.25M	2	230	1400	3.5	20	220-240V	1100W	TES2	1#
LFJX7.6/1.5M	2	230	1400	3.5	20	220-240V	1100W	TES2	2#
LFJX9.7/1.9M	3	230	2100	3.5	30	220-240V	1650W	TES2	2#
LFJX12/2.3M	3	230	2100	3.5	30	220-240V	1650W	TES2	3#
LFJX16/3.0M	3	230	2100	4	48	220-240V	1650W	TES2	3#

## LFJX系列吸顶式冷风机

### LFJX series ceiling type air cooler

库温Room temp.  $\geq -20^{\circ}\text{C}$ , 片距 Fin spacing 6.0mm R404A

配丹佛斯膨胀阀(默认 $T_c=-18^{\circ}\text{C}/7\text{KTD}$ ) With Danfoss expansion valve(default  $T_c=-18^{\circ}\text{C}/7\text{KTD}$ )

#### 技术数据 Technical Data

型号 Model	制冷量 Capacity(W)	面积 Surface	管容 Tube volume	接口尺寸(inch) Connection Dimension	外形尺寸(mm) External Dimension	安装尺寸(mm) Installation Dimension
-------------	--------------------	---------------	-------------------	------------------------------------	--------------------------------	------------------------------------

MODEL	Tc=-18°C/7KTD	m <sup>2</sup>	dm <sup>3</sup>	进口Inlet	出口Outlet	L	W	H	A	B
LFJX2.1/0.4L	400	2.1	0.85	3/8	5/8	530	545	210	497	525
LFJX2.5/0.5L	500	2.5	1.02	3/8	5/8	530	545	210	497	525
LFJX3.3/0.65L	650	3.3	1.32	3/8	5/8	650	545	210	617	525
LFJX4.0/0.8L	800	4	1.55	3/8	5/8	870	545	210	837	525
LFJX4.8/0.95L	950	4.8	1.86	3/8	5/8	870	545	210	837	525
LFJX6.1/1.2L	1200	6.1	2.33	3/8	5/8	1250	545	210	1217	525
LFJX7.3/1.5L	1500	7.3	2.8	3/8	5/8	1250	545	210	1217	525
LFJX9.8/2.0L	2000	9.8	3.75	3/8	5/8	1250	545	260	1217	525

型号 Model	风机 Fan						电热化霜	膨胀阀 Expansion Valve	阀芯 Orifice
	数量(台) Quantity	直径(mm) Diameter	风量(m <sup>3</sup> /h) Airflow	射程(m) Air Throw	输入功率(W) Input Power	电源 Voltage:50/60Hz	水盘Drain Pan		
LFJX2.1/0.4L	1	230	700	3.5	10	220-240V	580W	TES2	0#
LFJX2.5/0.5L	1	230	700	3.5	10	220-240V	580W	TES2	0#
LFJX3.3/0.65L	1	230	700	3.5	10	220-240V	760W	TES2	1#
LFJX4.0/0.8L	2	230	1400	3.5	20	220-240V	1100W	TES2	1#
LFJX4.8/0.95L	2	230	1400	3.5	20	220-240V	1100W	TES2	1#
LFJX6.1/1.2L	3	230	2100	3.5	30	220-240V	1650W	TES2	1#
LFJX7.3/1.5L	3	230	2100	3.5	30	220-240V	1650W	TES2	1#
LFJX9.8/2.0L	4	230	2100	4	48	220-240V	1650W	TES2	2#