



- * Hisilicon high-performance DSP
- * H.264 High profile dual stream
- * Standard ONVIF Protocol
- * Support motion detection, P2P, ONVIF
- * Support ICR filter switching function, day and night surveillance
- * Support remote control by smart phone, iphone/android
- * Support power supply DC12V
- * **APP: XMEYE**

Specification

Product Name	H.264 1.0/1.3/2.0MP P2P ONVIF Mini Full HD Car IP Camera		
Model No.	WDM-IP6475LA	WDM-IP6475LB	WDM-IP6475LH
Video			
System	Embedded linux		
Output resolution	1280(H)×720(V)	1280(H)×960(V)	1920(H)×1080(V)
D/N Mode	ICR-CUT		
Illumination	0.000LUX/F1.2(Led on)		
Video processing	H.264 video compression, dual streaming		
Video Output	Main streaming: 1280×720,1024×768,1280×720; Sub streaming: 1280×720, 960×540, 640×360, 480×270, 352×288, 320×240	Main streaming: 1280×960, 1280×720, 1024×768,1280×720; Sub streaming: 1280×720, 960×540, 640×360, 480×270, 352×288, 320×240	Main streaming: 1920×1080, 1280×960, 1280×720,1024×768,1280×720; Sub streaming: 1280×720, 960×540, 640×360, 480×270, 352×288, 320×240
Frame rate	1.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable	1.3MP 25/30 frame(full real time),support 1~30frame/seconds adjustable	2.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported		
Access Protocol	Standard ONVIF Protocol, Support third party access;		
	Support IE6.0 and above Smartphone		
	Support Android/iPhone		
Lens			
Lens	3.6mm		
Function			
Function	Support motion detection		
	Support front end storage ,playback and download		
	Support uniform client and platform system application		
Normal			
Power supply	DC12V		
Operation temperature	-10°C~+50°C		
Size	75mm*55mm*68mm		