


Combinable HD-Cvi/Tvi/Ahd Passive CCTV UTP BNC Video Balun		
	Specifications	
	Model	WDM-UTP6301HD
<p>WDM-UTP6301HD</p>	Transmission distance	
	CVBS	1200TVL / 650M
<p>Features</p> <ul style="list-style-type: none"> * Compatible with all HD-CVI, HD-TVI, HD-AHD Cameras and analog Cameras * No power required * 60dB cross talk and noise immunity * Compact size and easy installation * Built-in transient suppression protection * Innovative combinable design * Joining by screws video transfer 	HD-AHD	720P/550M, 1080P/350M
	HD-TVI	720P/500M, 1080P/300M
	HD-CVI	720P/550M, 1080P/350M
	Technical specifications	
	Wire Type	UTP5
	UTP Connection	"Press-Fit" terminal blocks
	Video Format	HD-CVI/TVI/AHD, NTSC, PAL, and SECAM
	Case	ABS Plastic
	Frequency Response	DC to 60MHz
	Attenuation	0.5dB typ
	CMRR	60 dB
	Surge protection	4KV
	ESD	8KV
	Power	No power required
	Working Temperature	-10°C to +50°C
	Storage Temperature	-30°C to +70°C
Humidity	0 to 95%	