

CCTV 16chs 2.0MP Security Real Surveillance Alarm DVR Systems



- * 1*16chs HD Dvr, 16chs video/network;
- * 8*outdoor 30m IR waterproof AHD cameras(Metal)
- * 8*indoor 30m IR Dome cameras(Plastic)
- * 16*18.3m(60 feet) Video+power cable
- * 1* 12v2A Power supply with 1 to 16 DC cable
- * Not included HDD

Model Number	WDM-CAHD16O-B	WDM-CAHD16K-B
AHD Cameras specifications		
Video		
Sensor	NVP2441H+Sony IMX307	FH8550M+Sony IMX327
Resolution	2.0MP (1920*1080)	
Minimum Illumination	0.000LUX/F1.2(Led on)	
Day/Night Mode	Color During day/switches to B&W at night	
Signal System	PAL/NTSC	
Effective Pixel	PAL: (1920*1080)@25fps; PAL: (1920*1080)@30fps	
Video Standard	AHD/TVI/CVI/1200TVL CVBS Standard	
WDR	Yes	
3D DNR	Yes	
WDR	—	—
3D DNR	—	Yes
Lens and IR		
Lens	3.6mm	
IR Distance	Up to 30m	
IR Cut Filter	yes	
General		
Waterproof	IP66	
Indoor / Outdoor	Suitable for Indoor or Outdoor use	
Power Input	DC12V1A (16pcs)	
Working Temperature	-10°C ~+60°C	
DVR Specifications		
Operating System	Embedded linux	
Video&Audio		
Video compression	H.264	
Encode	16*AHD 1080P	
Analog input	16*AHD 1080P	
Hybrid input	8*AHD 1080P(analog)+8*1080P(Network)	
Audio Input	16 RCA Input	
Audio Output	1 RCA Output	
Audio compression	G.711A	
Recording		
Compression Format	H.264	
Recording Modes	Manual/Motion/Schedule	
Hard drive	Internal SATA hard drive required for recording,support up to 4TB	
Network		
LAN Connection	YES	
Network Interface	RJ45	
Interface		
Video input	16ch BNC	
Video output	1ch VGA, 1ch HDMI	
USB	2* USB 2.0	
HDD	1*SATA port (Max 4TB/per)	
General		
Power Supply	DC 12V	
Back up method	External storage via USB	
Temperature/Humidity	-20°C+50°C; -10%-90%	
Remote Control	YES	
DVR Language		
Russian, English, Finnish, French, German, Greek, Italian, Japanese, Poland, Protugal, Spanish, Thai, Turkey Romanian, Slovakia, Czech, Arabic, Swedish and so on		