



- * Support 4/8/16CHS 8.0MP/16CHS 5.0MP Encoding
- * Support XVI,AHD, TVI,CVI, CVBS, IP video input
- * Support VGA maximum 1080P output, HDMI up to 4K output
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- * Support the Onvif protocol
- * Support WEB, CMS, VMS, MYEYE Platform
- * Mobile phone remote monitoring (iOS, Android)
- * Cloud services, P2P, alarm information push to phone
- * Support for more than twenty languages

Specifications

Product Name	4/8/16chs H.265+ 6 In 1 Network AHD DVR		
Model No.	WDM-DVR6504T-GL	WDM-DVR6508T-GL	WDM-DVR6516T-GS

System

Processor	Hi3521D	Hi3531D	Hi3531D
-----------	---------	---------	---------

Video

Video compression	H.265+		
Encode	4*8M@8fps(AHD); 4*5M@14fps(6 in 1); 4*4M@18fps(6 in 1);4*3M@21fps (6 in 1); 4*1080P(6 in 1)	8*8M@8fps(AHD); 8*5M@14fps(6 in 1); 8*4M@18fps(6 in 1);8*3M@21fps (6 in 1); 8*1080P(6 in 1)	16*5M@6fps(6 in 1); 16*4M@8fps(6 in 1); 16*3M@10fps(6 in 1); 16*1080P@18fps(6 in 1); 16*720P(6 in 1)
Decode	4*8M@6fps(AHD); 4*5M@8fps(6 in 1); 4*4M@8fps(6 in1); 4*3M@8fps (6 in 1); 4*1080P@8fps(6 in 1)	8*8M@6fps(AHD); 8*5M@8fps(6 in 1); 8*4M@8fps(6 in1); 8*3M@8fps (6 in 1); 8*1080P@8fps(6 in 1)	16*5M@6fps(6 in 1); 16*4M@8fps(6 in1); 16*3M@10fps(6 in 1); 16*1080P@18fps(6 in 1); 16*720P(6 in 1)
Multi-mode	Analog:4*8M; 4*5M Hybird:2*8M (analog) +2*8M (network) IP: 4*8M;8*1080P+8*960P;4*5M;4*3M	Analog:8*8M; 8*5M Hybird:4*8M (analog) +4*8M (network) IP: 8*3M ;4*5M	Analog:16*5M;16*4M;16*1080P Hybird:8*4M@6fps(analog)+8*4M (network) IP: 8*3M ;4*5M
Playback	4ch	8ch	16ch

Audio

Audio compression	G.711A		
-------------------	--------	--	--

Management

Record mode	Manual>Alarm>Motion detection>Timing		
Inquire mode	Inquire by Time/Calendar/Event/Channel		
Storage mode	HDD Storage, Network Storage		
Backup	Network, USB, SATA		

Interface

Video Input	4*BNC (Support Coaxitron)	8*BNC (Support Coaxitron)	16*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:4K)		
VGA output	1*VGA (MAX:1080P)		
Audio In/Out	4/1	4/1	4/1
Alarm In/Out	0/0		
Ethernet	1*10/100Mbps Ethernet port, RJ45 port		
PTZ Control	1*RS485, Support for multiple PTZ protocol		
USB	2*USB2.0		
HDD	1*SATA interface (Up to 8TB)		

General

Power supply	DC12V 2A
Consumption	<10W(Without HDD)
Working temperature	0℃--+55℃
Working humidity	10%--90%
Chassis	Mini 1 U