

2.0MP CCTV Video Surveillance IR Dome Fish-Eye 130°IP Vandalproof Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning Sony
- *H.264/H.265 High profile, Min. illumination 0.1lux
- *support dual stream, support mobile phone
- *support power supply DC12V/POE
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance

Dimension



Accessories

User Manual
CD
Screw fittings

Specification

Product Name	2.0MP CCTV Video Surveillance IR Dome Fisheye IP HD Camera
Model No.	WDM-HIP130DR/H
Video	
System	Hisilicon high-performance DSP, Hi3516EV100+SONY IMX323
Sensor	1/3" 2.0M Pixels Progressive Sony Image Sensor
Output resolution	1920(H)×1080(V)
D/N Mode	Auto switching, black and white vide and IR cut action linkage
Illumination	Color 1.0Lux@F1.2, Black 0.1 Lux@F1.2
Video processing	H.265 video compression, dual streaming
	AVI format, 0.1M~6Mbps adjustable;
Video Output	Main streaming: 1920*1080, 1280*960, 1280*720, 1024*768, 1280*720;
	Sub streaming: 960*540, 640*360, 480*270, 352*288, 320*240, 352*192, 320*192, 288*192, 256*192
Frame rate	2.0MP 25/30 frame(full real time), support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet, 10/100M; RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;
	Support IE6.0 and above Smartphone
	Support Android\iPhone
Lens	
Lens	130 degree lens
IR distance	10-15m(15pcs f5 IR leds)
Function	
Function	Support WEB configuration, OSD, real-time video transmission
	Support motion detection
	Support front end storage, playback and download
	Support uniform client and platform system application
	Support complete SDK for second development.
Normal	
Power supply	DC12V/POE(optional)
Operation temperature	-10°C~+60°C, 10%~90%RH