

CCTV 16chs 2.0MP Security Real Surveillance Alarm DVR Systems



- * 1*16chs HD Dvr, 16chs video/network;
- * 8*outdoor 30m IR waterproof AHD cameras
- * 8*indoor 30m IR Dome cameras
- * 16*18.3m(60 feet) Video+power cable
- * 1* 12v2A Power supply with 1 to 16 DC cable
- * Not included HDD

Model Number	WDM-YAHD16O-B	WDM-YAHD16P-B	WDM-YAHD16K-B
AHD Cameras specifications			
Video			
Sensor	NVP2441H+Sony IMX307	NVP2441H+Sony IMX291	FH8550M+Sony IMX290
Resolution	2.0MP (1920*1080)		
Minimum Illumination	0.000LUX/F1.2(Led on)		
Day/Night Mode	Color During day/switches to B&W at night		
Signal System	PAL/NTSC		
Effective Pixel	PAL: (1920*1080)@25fps; PAL: (1920*1080)@30fps		
Video Standard	AHD/TVI/CVI/1200TVL CVBS Standard		
WDR	Yes		
3D DNR	Yes		
WDR	—	—	Yes
3D DNR	—	Yes	Yes
Lens and IR			
Lens	3.6mm		
IR Distance	Up to 30m		
IR Cut Filter	yes		
General			
Waterproof	IP66		
Indoor / Outdoor	Suitable for Indoor or Outdoor use		
Power Input	DC12V1A (16pcs)		
Working Temperature	-10°C ~+60°C		
DVR Specifications			
Operating System	Embedded linux		
Video&Audio			
Video compression	H.264		
Encode	16*AHD 1080P		
Analog input	16*AHD 1080P		
Hybrid input	8*AHD 1080P(analog)+8*1080P(Network)		
Audio Input	16 RCA Input		
Audio Output	1 RCA Output		
Audio compression	G.711A		
Recording			
Compression Format	H.264		
Recording Modes	Manual/Motion/Schedule		
Hard drive	Internal SATA hard drive required for recording,support up to 4TB		
Network			
LAN Connection	YES		
Network Interface	RJ45		
Interface			
Video input	16ch BNC		
Video output	1ch VGA, 1ch HDMI		
USB	2* USB 2.0		
HDD	1*SATA port (Max 4TB/per)		
General			
Power Supply	DC 12V		
Back up method	External storage via USB		
Temperature/Humidity	-20°C+50°C; -10%-90%		
Remote Control	YES		
DVR Language			
Russian, English, Finnish, French, German, Greek, Italian, Japanese, Poland, Protugal, Spanish, Thai, Turkey Romanian, Slovakia, Czech, Arabic, Swedish and so on			