

CCTV 1.0MP IR Bullet Video Surveillance HD IP Security Camera



**Features**

- \*Hisilicon high-performance DSP
- \*High quality progressive scanning CMOS
- \*H.264 High profile
- \*support dual stream, support mobile phone
- \*support power supply DC12V/POE
- \*Standard ONVIF Protocol
- \*Complete SDK for second development. Support multi network protocols
- \*Provide a unified free client to achieve video recording/playback/preview
- \*Support ICR filter switching function, day and night surveillance
- \*Waterproof IP66

**Dimension**



**Accessories**

User Manual  
CD  
Screw fittings

**Specification**

|                                              |                                                                                                                                                 |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name                                 | CCTV 1.0MP IR Bullet Video Surveillance HD IP Camera                                                                                            |
| Model No.                                    | WDM-7746E                                                                                                                                       |
| <b>Video</b>                                 |                                                                                                                                                 |
| System                                       | Hisilicon high-performance DSP, XM510+H62                                                                                                       |
| Sensor                                       | 1/3" 1.0M Pixels Progressive CMOS Image Sensor                                                                                                  |
| Output resolution                            | 1280(H)×720(V)                                                                                                                                  |
| D/N Mode                                     | Auto switching, black and white vide and IR cut action linkage                                                                                  |
| Illumination                                 | Color 1.0Lux@F1.2, Black 0.1 Lux@F1.2                                                                                                           |
| Video processing                             | H.264 video compression, dual streaming<br>AVI format, 0.1M~6Mbps adjustable;                                                                   |
| Video Output                                 | Main streaming: 1280×720, 1024×768, 1280×720;<br>Sub streaming: 960×540, 640×360, 480×270, 352×288, 320×240, 352×192, 320×192, 288×192, 256×192 |
| Frame rate                                   | 1.0MP 25/30 frame(full real time), support 1~30frame/seconds adjustable                                                                         |
| Network interface                            | RJ45 ethernet, 10/100M; RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported                                                                    |
| Access Protocol                              | Standard ONVIF Protocol, Support third party access; PC;<br>Support IE6.0 and above Smartphone<br>Support Android/iPhone                        |
| <b>Lens</b>                                  |                                                                                                                                                 |
| Lens                                         | 2.8-12mm manual varifocal lens                                                                                                                  |
| IR distance                                  | 80m (72pcs f5 IR leds)                                                                                                                          |
| <b>Function</b>                              |                                                                                                                                                 |
| Function                                     | Support WEB configuration, OSD, real-time video transmission                                                                                    |
|                                              | Support motion detection                                                                                                                        |
|                                              | Support front end storage, playback and download                                                                                                |
|                                              | Support uniform client and platform system application                                                                                          |
| Support complete SDK for second development. |                                                                                                                                                 |
| <b>Normal</b>                                |                                                                                                                                                 |
| Power supply                                 | DC12V/POE(optional)                                                                                                                             |
| Operation temperature                        | -10℃~+60℃, 10%~90%RH                                                                                                                            |