

**Metal Dome CMOS Sony IMX178 H. 265 5.0MP IP Camera From Wardmay Ltd**



**Features**

- \*Hisilicon high-performance DSP
- \*High quality progressive scanning CMOS
- \*H.265 High profile
- \*support dual stream, support mobile phone
- \*support power supply DC12V/POE
- \*Standard ONVIF Protocol
- \*Complete SDK for second development. Support multi network protocols
- \*Provide a unified free client to achieve video recording/playback/preview
- \*Support ICR filter switching function, day and night surveillance

**Dimension**



**Accessories**

- User Manual
- CD
- Screw fittings

**Specification**

Product Name	<b>2017 Newest CMOS Sony IMX178 H. 265 5.0MP IP Camera From Wardmay</b>
Model No.	WDM-IP9723D / WDM-IP9723DL
<b>Video</b>	
System	Hisilicon high-performance DSP, Hi3516A+Sony IMX178
Sensor	1/1.8" 5.0M Pixels Progressive Sony IMX178 CMOS Image Sensor
Output resolution	2592(H)×1944(V)
D/N Mode	Auto switching,black and white vide and IR cut action linkage
Illumination	Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2
Video processing	H.265 video compression, dual streaming AVI format, 0.1M~6Mbps adjustable;
Video Output	Main streaming: 2592*1944, 2592*1520, 2048*1536, 1920*1080, 1280*960, 1280*720,1024*768,1280*720; Sub streaming: 960*540,640*360,480*270,352*288,320*240,352*192, 320*192,288*192,256*192
Frame rate	5.0MP 25 frame(full real time), support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported
Access Protocol	Standard ONVIF Protocol, Support third party access; PC; Support IE6.0 and aboveSmartphone Support Android/iPhone
<b>Lens</b>	
Lens	2.8-12mm lens
IR distance	30m(30pcs f5 IR leds)
Wifi	meet with IEEE 802.11b/g/n wireless standard, WEP & WPA
<b>Function</b>	
Function	Support WEB configuration, OSD,real-time video transmission Support motion detection Support front end storage ,playback and download Support uniform client and platform system application Support complete SDK for second development.
<b>Normal</b>	
Power supply	DC12V/POE(optional)
Operation temperature	-10°C~+60°C,10%~90%RH