

H.265 2.0MP CCTV Video Surveillance IR Dome IP HD Camera



Features

- * Hisilicon high-performance DSP
- * High quality progressive scanning CMOS
- * H.265/H.264 High profile
- * Support dual stream, support mobile phone
- * Support power supply DC12V/POE
- * Standard ONVIF Protocol, support multi network protocols
- * Metal case, Waterproof IP66

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification			
Product Name		H.265 2.0MP CCTV Video Surveillance IR Dome IP HD Camera	
Model No.		WDM-HIP8200A	WDM-HIP8200AH
Video			
System		Hi3516EV200+Sony IMX307	Hi3516D+Sony IMX290
Sensor		1/2.8" CMOS Sensor	
Output resolution		2.0MP(1920×1080)	
D/N Mode		Auto switching,black and white video and IR cut action linkage	
Illumination		Color: 0.001lux@F1.2; B/W: 0lux@F1.2	
SNR		≥50db(AGC OFF)	
Gain Control		Auto/ Manual	Auto
DNR		Support 2DNR, 3DNR	3DNR
WDR		DWDR(100dB)	>120dB
Video processing		H.265/H.264 video compression, dual streaming	
		AVI format, 0.7M~8Mbps adjustable;	32KB ~16Mbps, support VBR, CBR
Video Output	Main streaming	1920*1080,1280*960,1280*720	1920*1080,1280*720, D1,VGA,QVGA
	Sub streaming	800*448,640*480,640*360,352*288	D1, VGA, QVGA
Frame rate		2.0MP@30fps,support 7~30fps/s adjustable	1920*1080(1~25/30fps)
Network interface		RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported	
Access Protocol		Standard ONVIF Protocol, Support third party access; PC;	
		Support IE6.0 and above Smartphone	
		Support Android\iPhone	
Lens			
Lens		Standard 3.6mm lens(6mm lens optional)	
View Angle		3.6mm lens(2MP F2.0 1/2.8" H 85.7°); 6mm lens(2MP F2.0 1/2.8" H 52.7°)	
IR distance		15-20m(24pcs F5 IR leds)	
Function			
Function		Support WEB configuration, OSD,real-time video transmission	
		Support motion detection	
		Support front end storage ,playback and download	
		Support uniform client and platform system application	
		Support complete SDK for second development.	
Normal			
Material		Metal Case, White	
Weather Proof		IP66 Waterproof, Weather Resistance	
Power supply		DC12V/POE(18W) optional	
Operation temperature		-20°C~+60°C,10%~90%RH	