



Combinable HD-Cvi/Tvi/Ahd Passive CCTV UTP BNC Video Balun					
			Specifications		
			<table border="1"> <tr> <td>Model</td> <td>WDM-UTP6501VP/WDM-UTP6701VP</td> </tr> </table>	Model	WDM-UTP6501VP/WDM-UTP6701VP
Model	WDM-UTP6501VP/WDM-UTP6701VP				
			Transmission distance		
			<table border="1"> <tr> <td>Video signal</td> <td>350M-550M</td> </tr> </table>	Video signal	350M-550M
Video signal	350M-550M				
WDM-UTP6501VP		WDM-UTP6701VP	<table border="1"> <tr> <td>Power signal</td> <td>200M-300M</td> </tr> </table>	Power signal	200M-300M
Power signal	200M-300M				
<div style="background-color: #ff4500; color: white; padding: 5px; border-radius: 10px; display: inline-block;">Features</div> <ul style="list-style-type: none"> * Compatible with all HD-CVI, HD-TVI, HD-AHD Cameras and analog Cameras * No power required * 60dB cross talk and noise immunity * Compact size and easy installation * Built-in transient suppression protection * Super strong anti-jamming device, lightning proof * Joining by screws video transfer 			<table border="1"> <tr> <td>Audio signal</td> <td>350M-550M</td> </tr> </table>	Audio signal	350M-550M
Audio signal	350M-550M				
			Technical specifications		
			<table border="1"> <tr> <td>Wire Type</td> <td>UTP5</td> </tr> </table>	Wire Type	UTP5
Wire Type	UTP5				
			<table border="1"> <tr> <td>UTP Connection</td> <td>"Press-Fit" terminal blocks</td> </tr> </table>	UTP Connection	"Press-Fit" terminal blocks
UTP Connection	"Press-Fit" terminal blocks				
			<table border="1"> <tr> <td>Video Format</td> <td>HD-CVI/TVI/AHD, NTSC, PAL, and SECAM</td> </tr> </table>	Video Format	HD-CVI/TVI/AHD, NTSC, PAL, and SECAM
Video Format	HD-CVI/TVI/AHD, NTSC, PAL, and SECAM				
			<table border="1"> <tr> <td>Case</td> <td>ABS Plastic</td> </tr> </table>	Case	ABS Plastic
Case	ABS Plastic				
			<table border="1"> <tr> <td>Frequency Response</td> <td>DC to 60MHz</td> </tr> </table>	Frequency Response	DC to 60MHz
Frequency Response	DC to 60MHz				
			<table border="1"> <tr> <td>Attenuation</td> <td>0.5dB typ</td> </tr> </table>	Attenuation	0.5dB typ
Attenuation	0.5dB typ				
			<table border="1"> <tr> <td>CMRR</td> <td>60 dB</td> </tr> </table>	CMRR	60 dB
CMRR	60 dB				
			<table border="1"> <tr> <td>Surge protection</td> <td>4KV</td> </tr> </table>	Surge protection	4KV
Surge protection	4KV				
			<table border="1"> <tr> <td>ESD</td> <td>8KV</td> </tr> </table>	ESD	8KV
ESD	8KV				
			<table border="1"> <tr> <td>Power</td> <td>DC12V</td> </tr> </table>	Power	DC12V
Power	DC12V				
			<table border="1"> <tr> <td>Working Temperature</td> <td>-10°C to +50°C</td> </tr> </table>	Working Temperature	-10°C to +50°C
Working Temperature	-10°C to +50°C				
			<table border="1"> <tr> <td>Storage Temperature</td> <td>-30°C to +70°C</td> </tr> </table>	Storage Temperature	-30°C to +70°C
Storage Temperature	-30°C to +70°C				
			<table border="1"> <tr> <td>Humidity</td> <td>0 to 95%</td> </tr> </table>	Humidity	0 to 95%
Humidity	0 to 95%				