

H.265 4.0MP CCTV Video Surveillance IR Dome IP HD Camera



Features

- \* Hisilicon high-performance DSP
- \* High quality progressive scanning CMOS
- \* H.265/H.264 High profile
- \* Support dual stream, support mobile phone
- \* Support power supply DC12V/POE
- \* Standard ONVIF Protocol, support multi network protocols
- \* Metal case, Waterproof IP66

Dimension



Accessories

- User Manual
- CD
- Screw fittings

| Specification         |                |                                                                            |
|-----------------------|----------------|----------------------------------------------------------------------------|
| Product Name          |                | H.265 4.0MP CCTV Video Surveillance IR Dome IP HD Camera                   |
| Model No.             |                | WDM-HIP8400A                                                               |
| Video                 |                |                                                                            |
| System                |                | Hi3516D+OV4689                                                             |
| Sensor                |                | 1/3" 4.0M Pixels Progressive CMOS Image Sensor                             |
| Output resolution     |                | 4.0MP(2592x1520)                                                           |
| D/N Mode              |                | Auto switching,black and white video and IR cut action linkage             |
| Illumination          |                | 0.05Lux/F1.2 (Color), 0.01Lux/F1.2(B/W)                                    |
| SNR                   |                | ≥50db(AGC OFF)                                                             |
| Gain Control          |                | Auto                                                                       |
| DNR                   |                | 3DNR                                                                       |
| WDR                   |                | DWDR(>80dB)                                                                |
| Video processing      |                | H.265/H.264 video compression, dual streaming                              |
|                       |                | 32KB ~16Mbps, support VBR, CBR                                             |
| Video Output          | Main streaming | 2592*1520,2048*1520,1920*1080,704*576,640*480,320*240                      |
|                       | Sub streaming  | 704*576,640*480,320*240                                                    |
| Frame rate            |                | 2592*1520(1~15fps); 2048*1520/1080P(1 ~ 25/30fps)                          |
| Network interface     |                | RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported |
| Access Protocol       |                | Standard ONVIF Protocol, Support third party access; PC;                   |
|                       |                | Support IE6.0 and above Smartphone                                         |
|                       |                | Support Android\iPhone                                                     |
| Lens                  |                |                                                                            |
| Lens                  |                | Standard 3.6mm lens(6mm lens optional)                                     |
| View Angle            |                | 3.6mm lens(4MP F2.0 1/3" H 76.1°); 6mm lens(4MP F2.0 1/3" H 49.5°)         |
| IR distance           |                | 15-20m(24pcs F5 IR leds)                                                   |
| Function              |                |                                                                            |
| Function              |                | Support WEB configuration, OSD,real-time video transmission                |
|                       |                | Support motion detection                                                   |
|                       |                | Support front end storage ,playback and download                           |
|                       |                | Support uniform client and platform system application                     |
|                       |                | Support complete SDK for second development.                               |
| Normal                |                |                                                                            |
| Material              |                | Metal Case, White                                                          |
| Weather Proof         |                | IP66 Waterproof, Weather Resistance                                        |
| Power supply          |                | DC12V/POE(18W) optional                                                    |
| Operation temperature |                | -20°C~+60°C,10%~90%RH                                                      |