



- * Using the high performance sensor, image is clear and delicate;
- * Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- * AHD/TVI/CVI/1200TVL 4 in 1 video output;
- * can access to many brands HD DVR;
- * Support the ultra low illumination;
- * Support automatic electronic shutter function, adapt to different monitoring environment;
- * 30m night vision distance, 30pcs F5 ir led , DC12V
- * 4" steel vandalproof dome. Waterproof:IP65

Specification

Product Name	CCTV 4X Zoom 2.0/5.0MP HD Video Security Surveillance IR Dome AHD Camera			
Model No.	WDM-AHD6136UZ	WDM-AHD6136PZ	WDM-AHD6136KZ	WDM-AHD6136QZ
Video				
Sensor	NVP2441H+Sony IMX323	NVP2441H+Sony IMX291	FH8550M+Sony IMX290	FH8538M+Sony IMX326
Output resolution	2.0MP (1920*1080)			5.0MP(2952*1944)
D/N Mode	IR cut Auto switching			
WDR	-	-	Support	-
DNR	3D DNR	3D DNR	3D DNR	3D DNR
Minimum Illumination	0.000LUX/F1.2(Led on)			
Effective Pixel	PAL: (1920*1080)@25fps			
	NTSC: (1920*1080)@30fps			
Signal System	PAL/NTSC			
Video Standard	AHD/TVI/CVI/CVBS standard			
Video Output	1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable)			
Max Transmission Distance	Common 75-3 cables can be up to 500m			
Lens and IR				
Lens	4X Zoom, 2.8-12mm manual iris lens			
IR distance	30m night vision distance, 30pcs F5 ir led			
Function				
Shutter Speed	4/25s-1/45,000s			
BLC	Off/Low/Medium/High/Highest			
White Balance	Auto White Balance			
HLC	Support			
Operation Temperature	-10℃~55℃			
Power Supply	DC12V			