

H.265 4.0/5.0MP CCTV Video Surveillance IR Bullet IP HD Camera



Features

- * Hisilicon high-performance DSP
- * High quality progressive scanning CMOS
- * H.265/H.264 High profile
- * Support dual stream, support mobile phone
- * Support power supply DC12V/POE
- * Standard ONVIF Protocol, support multi network protocols
- * Metal case, Waterproof IP65

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification	
Product Name	H.265 4.0/5.0MP CCTV Video Surveillance IR Bullet IP HD Camera
Model No.	WDM-HIP9400EH
Video	
System	Hi3516EV300+Sony IMX335
Sensor	1/2.8" 4.0/5.0M Pixels Progressive CMOS Image Sensor
Output resolution	5.0MP(2592x1944), 4.0MP(2592x1520)
D/N Mode	Auto switching,black and white video and IR cut action linkage
Illumination	0.001Lux@F1.2 (Color), 0Lux@F1.2(B/W)
SNR	≥50db(AGC OFF)
Gain Control	Auto
DNR	2D, 3DNR
WDR	DWDR
Video processing	H.265/H.264 video compression, dual streaming
	AVI format, 0.5M~8Mbps adjustable;
Video Output	Main streaming 2592*1944,2592*1520,2560*1440,2048*1520,2304*1296,1920*1080
	Sub streaming 800*448,720*480,640*480,640*360,480*360,352*288
Frame rate	2592*1944@15fps, 2592*1520@25fps
Network interface	RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;
	Support IE6.0 and above Smartphone
	Support Android\iPhone
Lens	
Lens	Standard 2.8-12 mm Manual Lens(5-50 mm Manual Lens optional)
View Angle	2.8-12 mm Manual Lens(6MP F1.3 1/2.7" H 113.54°-31.68°); 5-50 mm Manual Lens(F1.6 1/3.0" H 41.8°-6.4°)
Function	
Function	Support WEB configuration, OSD,real-time video transmission
	Support motion detection
	Support front end storage ,playback and download
	Support uniform client and platform system application
	Support complete SDK for second development.
Normal	
Material	Metal Case, White
Weather Proof	IP65 Waterproof
Power supply	DC12V/POE(24W) optional
Operation temperature	-20°C~+60°C,10%~90%RH