

4CHS WIFI NVR System From Wardmay Professional CCTV Camera Suppliers



4*960P

Video input (IP)

- * 4CH 720P/1080P WiFi NVR
- * Indoor/outdoor 20-30m WIFI 1.0/2-0 Megapixel IR waterproof IP cameras with adaptor, bracket.
- * Plug and Play,no need network paring
- * strong ability of singnal transmit up to crossing 1 to 4 walls, wifi distance:80-300 meters
- * APP: XMEye

IP Cameras specifications			
Model	WDM-NKITR904HDE-XM	WDM-NKITR904HE-XM	
Operating System	Embedded linux		
Image Sensor	XM510+H62 1/4" Progressive Scan Sensor	HI3516EV100+SC2235P 1/3" Progressive Scan Sensor	
Resolution	720P	1080P	
Frame Specification	H.264+ 1280*720@25fps	H.265+ 1920x1080@25fpS	
S/N Ratio	>39.1dB		
Minimum Illumination	Color:0.1 Lux; B/W:0.01 Lux		
Lens	3.6MM		
Infrared distance	20-30m		
Waterproof	IP66		
White Balance	Auto		
Day&Night	IR cut filter with auto switch		
3D-DNR	Auto		
Privacy Masking	4 Zone Selectable		
Infrared lamp	3pcs X ⊄ 20 Lamp beads		
Power Input	DC12V1A (4pcs)		
Consumption	max 6W		
Interface	RJ45/WIFI 802.11b/g/n		
Operation temperature	-10°C to +50°C /30% to 80% RH		
Size & Weight	170mm*65mm; 0.35KG		
WIFI NVR Specifications			
System			
Operating System	Embedded linux OS		
Main processor	Hi 3520D	Hi 3536D	
System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup		
Interface			
Operator interface	16-bit true color graphic menu operation interface, support mouse operation		
Preview	1/4		

4*1080P

Access bandwidth	24Mbps		
Forwarding bandwidth	25Mbps		
Video compression	H.264	H.265+	
Display quality	Max 960P	Max 1080P	
Playback quality	960P	1080P	
Decode	4*960P	4*1080P	
VR	Unsupport		
Motion detection	Support(depend on camera)		
Audio			
Audio compression	G.711A		
Intercom	Unsupport		
Record & playback	Record & playback		
Recording mode	Manual>Alarm>Dynamic Detection>Timing		
Local payback	4*960P	4*1080P	
Search mode	Search by Time/Calendar/Event/Channel		
Record storage	HDD、Network		
Backup mode	Network backup, USB hard disk, USB burner, SATA burner		
External Interface			
Video output	1ch VGA, 1ch HDMI HD output		
Audio I/O	0/0		
Alarm I/O	0/0		
Network interface	1*RJ45 10M/100M Adaptive Ethernet port+4ch WIFI		
USB interface	2*USB2.0 ports		
HDD	1* SATA(Up to 8TB for each disk)		
ESATA	No		
Serial interface	No		
Other			
ONVIF	No		
Power supply	12V/2A		
Power Consumption	<10W(Without HDD)		
Work environment	Temperature:0°C-+55°C , Humidity:10%−90%RH , Atm:86kpa−106kp		
Dimension	254mm*215mm*42mm		
Weight	1.05KG		
Package Informations			
Wifi NVR	1 set		
Wifi Camera	4 pieces		
Network line	1m*1		
Power adapter	DC12V2A(1 pcs); DC12V1A(4 pcs)		
USB Mouse	1 piece		
User Manual	1 piece		
Screw bag	4 pieces		
Weight	3.5KG		
Package Size	360mmx200mmx290mm		