

H.264 1.3MP 4" IR Dome Video Surveillance IP HD Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning CMOS
- *H.264 High profile
- *support dual stream, support mobile phone
- *support power supply DC12V/POE
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance
- *Metal case

Dimension



Accessories

User Manual
CD
Screw fittings

Specification	
Product Name	H.264 1.3MP 4" IR Dome Video Surveillance IP HD Camera
Model No.	WDM-IP7836E
Video	
System	Hisilicon high-performance DSP, XM510+H65
Sensor	1/3" 1.3M Pixels Progressive CMOS Image Sensor
Output resolution	1280(H)×960(V)
D/N Mode	Auto switching, black and white vide and IR cut action linkage
Illumination	Color 1.0Lux@F1.2, Black 0.1 Lux@F1.2
Video processing	H.264 video compression, dual streaming
	AVI format, 0.1M~6Mbps adjustable;
Video Output	Main streaming: 1280*960, 1280×720, 1024×768, 1280×720;
	Sub streaming: 960×540, 640×360, 480×270, 352×288, 320×240, 352×192, 320×192, 288×192, 256×192
Frame rate	1.3MP 25/30 frame(full real time), support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet, 10/100M; RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;
	Support IE6.0 and above Smartphone
	Support Android/iPhone
Lens	
Lens	4mm fixed lens
IR distance	20m(24pcs f5 IR leds)
Function	
Function	Support WEB configuration, OSD, real-time video transmission
	Support motion detection
	Support front end storage , playback and download
	Support uniform client and platform system application
	Support complete SDK for second development.
Normal	
Power supply	DC12V/POE(optional)
Operation temperature	-10°C~+60°C, 10%~90%RH