



- * Support 16ch 5M unreal-time encoding
- * Support Xvi,AHD, TVI,CVI, CVBS, IP video input
- * Support VGA maximum 1080P output, HDMI up to 4K output
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- * Support the Onvif protocol
- * Support WEB, CMS, VMS, MYEYE Platform
- * Mobile phone remote monitoring (iOS, Android)
- * Cloud services, P2P, alarm information push to phone
- * Support for more than twenty languages

Specifications

Product Name	16chs 5.0MP 6 In 1 Network AHD DVR
Model No.	WDM-DVR6516F-GS

System

Processor	Hi3531D
-----------	---------

Video

Video compression	H.265+
Encode	16*5M@6fps(6 in 1); 16*4M@8fps(6 in 1); 16*3M@10fps(6 in 1); 16*1080P@12fps(6 in 1); 16*720P(6 in 1)
Decode	16*5M@6fps(6 in 1); 16*4M@8fps(6 in 1); 16*3M@10fps(6 in 1); 16*1080P@12fps(6 in 1); 16*720P(6 in 1)
preview	16*5M@12.5fps(6 in 1); 16*4M@15fps(6 in 1); 16*3M@18fps(6 in 1); 16*1080P(6 in 1)
Multi-mode	Analog: 16*4M; 16*1080P
	Hybird:8*4M (analog)+8*4M (network)
	IP: 8*3M ;4*5M
Playback	16ch

Audio

Audio compression	G.711a
Intercom	Support

Management

Record mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA

Interface

Video Input	16*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:4K)
VGA output	1*VGA (MAX:1080P)
Audio In/Out	16/1
Alarm In/Out	16/4
Ethernet	1*10/100Mbps Ethernet port, RJ45 port
PTZ Control	1*RS485, Support for multiple PTZ protocol
USB	2*USB2.0 ports
HDD	4*SATA interface (Up to 6TB)

General

Power supply	12V/6A
Consumption	<10W (Without HDD)
Working temperature	0 ℃ - + 55 ℃
Working humidity	10% -90% RH
Chassis	Mini 1.5U