

4CHS WIFI NVR Kits with 15" LCD monitor (Model: WDM-NKITR04DWL-15)



- * 4CH 960P/1080P WiFi NVR with 12" LCD Screen
- * Indoor/outdoor 20-30m WIFI 1.0/2-0 Megapixel IR waterproof IP cameras with adaptor, bracket.
- * Plug and Play,no need network paring
- * strong ability of singnal transmit up to crossing

8) 6 8)		ity of singnal transmit up to crossing s, wifi distance:80-300 meters ye		
IP Cameras specifications				
Operating System	Embedded linux			
Image Sensor	1.3MP 1/3" Progressive Scan Sensor	2.0 MP 1/3" Progressive Scan Sensor		
Resolution	960P	1080P		
Frame Specification	H.264 1280*720@25fps	H.264 1920x1080@25fps		
S/N Ratio	>39.1dB			
Minimum Illumination	Color:0.1 Lux; B/W:0.01 Lux			
Lens	3.6MM			
Infrared distance	20-30m			
Waterproof	IP66			
White Balance	Auto			
Day&Night	IR cut filter with auto switch			
3D-DNR	Auto			
Privacy Masking	4 Zone Selectable			
Infrared lamp	3pcs X ⊄ 20 Lamp beads			
Power Input	DC12V1A (4pcs)			
Consumption	max 6W			
Interface	RJ45/WIFI 802.11b/g/n			
Operation temperature	-10°C to +50°C /30% to 80% RH			
WIFI NVR Specification	us .			
System				
Operating System	Embedded linux OS			
Main processor	Hi 3520D	Hi 3536D		
System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup			
Interface				
Operator interface	16-bit true color graphic menu operation interface, support mouse operation			
Preview	1/4			
Video input (IP)	4*960P	4*1080P		
Access bandwidth	24Mbps			
Forwarding bandwidth	25Mbps			
Video compression	H.264	H.265+		
Display quality	Max 960P	Max 1080P		
Playback quality	960P	1080P		
Decode	4*960P	4*1080P		
VR	Unsupport			
Motion detection	Support(depend on camera)			
Audio				
Audio compression	Audio compression G.711A			

December 9 mlayback		
	Intercom	Unsupport
	Audio compression	G.711A

Record & playback Recording mode

Backup mode	Network backup, USB hard disk, USB burner, SATA burner	
Record storage	HDD、Network	
Search mode	Search by Time/Calendar/Event/Channel	
Local payback	4*960P	4*1080P
Recording mode	Manual>Alarm>Dynamic Detection>Timing	

1ch VGA, 1ch HDMI HD output

External Interface Video output

Audio I/O	0/0
Alarm I/O	0/0
Network interface	1*RJ45 10M/100M Adaptive Ethernet port+4ch WIFI
USB interface	2*USB2.0 ports
HDD	1* SATA(Up to 8TB for each disk)
ESATA	No
Serial interface	No
Other	
ONVIE	No

ONVIF	No
Power supply	12V/2A
Power Consumption	<10W(Without HDD)
Work environment	Temperature:0℃-+55℃,Humidity:10%−90%RH,Atm:86kpa−106kp

Package Informations

Screw bag

4 pieces

Wifi NVR	1 set
Camera	4 pieces
Network line	1m*1
Power adapter	DC12V2A(1 pcs); DC12V1A(4 pcs)
USB Mouse	1 piece
User Manual	1 piece
Network line Power adapter USB Mouse	1m*1 DC12V2A(1 pcs); DC12V1A(4 pcs) 1 piece