



- * Support 64/128chs 4K Video access storage
- * Support H.265+/H.265/H.264, support i8S super protocol, plug and play.
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- * Support ONVIF Protocol; support GB28181 Protocol (Optional)
- * Support WEB, CMS, VMS, MYEYE Platform, provide SDK for develop
- * Support Mobile Phone Monitoring (IOS, Android)
- * Cloud Services, P2P, Alarm Information Push To Phone
- * supports max 8channels intelligent analysis locally (target counting, item detection, area detection, virtual warning line)

Specifications

Product Name	Wdm Security 3U 64/128chs 4K Network Security NVR	
Model No.	WDM-NVR886416MD	WDM-NVR8812816MD

Video and Audio

Network video input	64chs network compressed video input (MAX:4K)	128chs network compressed video input (MAX:4K)
Access bandwidth	640M	
Audio input	IPC compound audio input	
HDMI/Output	1*HDMI, 1*VGA, Resolution: 3840×2160/30Hz, 1920×1080/60Hz, 1280×1024/60Hz	
Audio output	1*RCA	
Video compression	H.265+/H.265/H.264 /MJPEG	
Resolution	12M/8M/5M/3M/1080P/720P	
Playback	4*4K; 16*1080P	

Management

Record/Screenshot mode	Manual>Timing>Event>Motion detection>Alarm>Motion detect or Alarm>Motion detect and Alarm
Playbakc mode	Instant playback, regular playback, event playback, external file playback, log playback
Storage mode	HDD Storage, Network Storage
Backup	General backup, event backup, Video clip backup

Interface

Ethernet	2*10/100Mbps Ethernet port, RJ45 port
serial interface	Full duplex standard RS-485 interface
Alarm In/Out	16/8
Audio In/Out	1/1
USB	3*USB, 2 USB2.0 interface front, 1 USB3.0 interface post
HDD	16*SATA interface + 1*eSATA(Up to 8TB)

Network

Networking protocol	ONVIF, IPv4, UPnP, NTP, SADP, PPoE, DHCP, etc
---------------------	---

General

Power supply	ATX110-220V 300W 50-60Hz
Consumption	<50W (Without HDD)
Working temperature	0℃ - + 55℃
Working humidity	10% -90% RH
Chassis	NVR: 437mmx483mmx143mm
	Package: 600mmx556mmx275mm
Weight(without HDD)	Net weight: 18.5 kg