


H.264 1.0/1.3MP CCTV Video Security Surveillance IR Dome IP Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning CMOS
- *H.264 High profile
- *support dual stream, support mobile phone
- *support power supply DC12V/POE(optional)
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance
- * Plastic case

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification		
Product Name	H.264 1.0/1.3MP CCTV Video Security Surveillance IR Dome IP Camera	
Model No.	WDM-7762E	WDM-7862E
Video		
System	Hisilicon high-performance DSP, XM510+H62	Hisilicon high-performance DSP, XM510+H65
Sensor	1.0M Pixel 1/3" CMOS Sensor	1.3M Pixel 1/3" CMOS Sensor
Output resolution	1280(H)×720(V)	1280(H)×960(V)
D/N Mode	Auto switching,black and white vide and IR cut action linkage	
Illumination	Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2	
Video processing	H.264 video compression, dual streaming	
	AVI format, 0.1M~6Mbps adjustable;	
Video Output	Main streaming: 1280×720,1024×768,1280×720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192, 320×192,288×192,256×192	Main streaming: 1280×960,1280×720,1024×768,1280×720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192, 320×192,288×192,256×192
	Frame rate	1.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported	
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;	
	Support IE6.0 and aboveSmartphone	
	Support Android/iPhone	
Lens		
Lens	3.6/6mm lens	
IR distance	30m(36pcs f5 IR leds)	
Function		
Function	Support WEB configuration, OSD,real-time video transmission	
	Support motion detection	
	Support front end storage ,playback and download	
	Support uniform client and platform system application	
	Support complete SDK for second development.	
Normal		
Power supply	DC12V/POE(optional)	
Operation temperature	-10°C~+60°C,10%~90%RH	