


CCTV 2.0MP IR HD Mini Video Digital Surveillance Dome Camera					
	<b>Specification</b>				
	Product Name	CCTV 2.0MP IR HD Mini Video Digital Surveillance Dome Camera			
	Model No.	WDM-AHD6714G WDM-AHD6714S WDM-AHD6714U	WDM-AHD6714H	WDM-AHD6714P	WDM-AHD6714K
	<b>Video</b>				
	Sensor	XM330+2235 FH8536+AR0232 V30E+Sony IMX323	NVP2441H+Sony IMX322	NVP2441H+Sony IMX291	FH8550M+Sony IMX290
	Output resolution	2.0MP(1920x1080)			
	D/N Mode	IR cut Auto switching			
	WDR	-	-	-	Support
	DNR	2D DNR	3D DNR	3D DNR	3D DNR
	Minimum Illumination	0.000LUX/F1.2(Led on)			
Effective Pixel	PAL: (1920*1080)@25fps	PAL: (1920*1080)@25fps	PAL: (1920*1080)@25fps	PAL: (1920*1080)@25fps	
	NTSC: (1920*1080)@30fps	NTSC: (1920*1080)@30fps	NTSC: (1920*1080)@30fps	NTSC: (1920*1080)@30fps	
Signal System	PAL/NTSC				
Video Standard	AHD/TVI/CVI/CVBS standard				
Video Output	1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable)				
Max Transmission Distance	Common 75-3 cables can be up to 500m				
<b>Lens and IR</b>					
Lens	3.6mm lens				
<b>Function</b>					
Shutter Speed	4/25s-1/45,000s				
BLC	Off/Low/Medium/High/Highest				
White Balance	Auto White Balance				
HLC	Support				
Operation Temperature	-10°C~55°C				
Power Supply	DC12V				
<b>Features</b>					
1. Just looks like smoke detector, not the real smoke detector					
2. Using the high performance sensor, image is clear and delicate;					
3. Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;					
4. Analog HD 2.0MP AHD video output;					
5. Support the ultra low illumination;					
6. Support automatic electronic shutter function, adapt to different monitoring environment;					
7. 3.6mm lens , DC12V					
8. White					
<b>Accessories</b>					
User Manual					
Warranty Card					
Screw fittings					
Desiccant					