

H.264 1.3MP IR Bullet Video Surveillance IP HD Security Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning CMOS
- *H.264 High profile
- *support dual stream, support mobile phone
- *support power supply DC12V/POE
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance
- *Waterproof IP66

Dimension



Accessories

User Manual
CD
Screw fittings

Specification

Product Name	H.264 1.3MP IR Bullet Video Surveillance IP HD Camera
Model No.	WDM-7846E
Video	
System	Hisilicon high-performance DSP, XM510+H65
Sensor	1/3" 1.3M Pixels Progressive CMOS Image Sensor
Output resolution	1280(H)×960(V)
D/N Mode	Auto switching, black and white vide and IR cut action linkage
Illumination	Color 1.0Lux@F1.2, Black 0.1 Lux@F1.2
Video processing	H.264 video compression, dual streaming AVI format, 0.1M~6Mbps adjustable;
Video Output	Main streaming: 1280*960, 1280*720, 1024*768, 1280*720; Sub streaming: 960*540, 640*360, 480*270, 352*288, 320*240, 352*192, 320*192, 288*192, 256*192
Frame rate	1.3MP 25/30 frame(full real time), support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet, 10/100M; RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported
Access Protocol	Standard ONVIF Protocol, Support third party access; PC; Support IE6.0 and above Smartphone Support Android/iPhone
Lens	
Lens	2.8-12mm varifocal lens
IR distance	80m(72pcs f5 IR leds)
Function	
Function	Support WEB configuration, OSD, real-time video transmission Support motion detection Support front end storage , playback and download Support uniform client and platform system application Support complete SDK for second development.
Normal	
Power supply	DC12V/POE(optional)
Operation temperature	-10°C~+60°C, 10%~90%RH