## Helper <sub>汉普机械</sub>

## **Bowl Cutter Series**







- --- Cutting in vacuum environment, It prevents the raw meat of myoglobin, fat and other nutrients from oxidized damage and reduces the bubbles existing.
- --- The high speed cutting system make it possible to produce homogenized meats with relatively shorter time and less temperature rising.
- --- Excellent cutting result due to the best combination of knife and pot speed. Distance is less than 2mm between the cutting knife and cutting pot.
- --- Key parts produced by advanced machine processing center.
- --- Temperature monitoring and control.
- --- Mechanical loading for 200 litre buggies and automatic discharging devices made it easy for dealing with raw materials at production.

Model	Capacity (kg)	Volume (L)	Power (kw)	Knife quantity	Bowl speed (r/min)	Unloader spe (r/min)	eed Knife speed (r/min)	Weight (kg)	Dimension (mm)
ZB-40	25	40	4.75	3	12/24	1	1450/2890	500	1020×840×1130
ZB-80	70-75	80	11	6	7/11	88	750/1500/3000	1300	1900×1500×1500
ZB-125	100-110	125	33.2	6	7/11	88	300/1500/3000/4500	2000	2100×1420×1600
ZB-200	170-180	200	60	6	7.5/10/15	82	200/1800/3600	3500	2950×2400×1950
ZKZB-200	170-180	200	65	6	7.5/10/15	stepless	300/1800/3600/4500	4800	3100×2420×2300
ZB-330	270-310	330	82	6	6/12	stepless	300/1800/3600/4500	5000	3855×2900×2100

## **Meat Mixer Series**

- --- Excellent and Mature vacuum sealing technology that applied in the whole mixing machine series.
- --- The cycloidal gear of this machine makes transmission stable reliable, and low noise.
- --- Single and double shaft structure are available for different capacities.
- --- It prevents the raw meat to be oxidized damage and reduces the bubbles existing.
- --- Auto cover opening and closing and easy material discharging design.
- --- Positive and inversive rotation control.
- --- Cooling system is an optional for special application.
- --- Stainless steel structure and excellent surface







Model	Volume (L)	Power (kw)	Mixing speeds (r/min)	Weight (kg)	Dimension (mm)
ZKJB-60	60	1.5	75/37.5	260	1060×600×1220
ZKJB-150	150	2.4+1.1	80/40	430	1360×680×1200
ZKJB-300	300	2.4×2+1.1	84/42	600	1190×1010×1447
ZKJB-650	650	4.5×2+1.1	84/42	850	1553×1300×1568
ZKJB-800	800	4.5×2+1.1	84/42	1100	2100×1380×1860
ZKJB-1200	1200	7.5×2+2.2	84/42	1760	2160×1500×2000