

**Twin Eyes
TE200**

NO FIELD CALIBRATION


Mobile: Fit for a variety of venues and multi-station.

All-round machine, without installation.


Support Multi-screen Display. All data can be shown on LCD, cell phone with android system and tablet PC simultaneously.

MOBILE 3D WHEEL ALIGNMENT WITHOUT INSTALLATION

DOUBLE SCISSOR LIFT



Place and Push car



Lift and adjustment



MEASUREMENT RANGE AND ACCURACY

References	Accuracy	Measurement Range
Camber	$\pm 0.01^\circ$	$\pm 8^\circ$
Caster	$\pm 0.03^\circ$	$\pm 19^\circ$
Front Wheel K.P.I	$\pm 0.02^\circ$	$\pm 19^\circ$
Toe	$\pm 0.01^\circ$	$\pm 2^\circ$
Rear Wheel Thrust Angle	$\pm 0.02^\circ$	$\pm 2^\circ$
Rear Axle Deviation	$\pm 0.02^\circ$	$\pm 2^\circ$

References	Accuracy	Measurement Range
Track width Difference	$\pm 0.02^\circ$	$\pm 2^\circ$
Front Setback	$\pm 0.02^\circ$	$\pm 2^\circ$
Rear Setback	$\pm 0.02^\circ$	$\pm 2^\circ$
Track Width	$\pm 0.64\text{cm}$	$< 265\text{cm}$
Wheelbase	$\pm 0.64\text{cm}$	$< 533\text{cm}$