

## TLFZ Non-expandable Dacron Seamless Textile Sleeve

### Description

TLFZ Non-expandable Dacron Textile Sleevings is weaved by high-performance Dacron multifilament.

It has the characteristics of excellent stretch resistance, corrosion resistance, explosion proof, abrasion proof, reducing noise, moisture absorption, dust proof, etc.



### Product application

Dacron non-shrinkable textile sleeving is mainly used in hydraulic tube, oil tube, air tube and other tube materials of mechanical equipment for explosion protection.



### Technical parameters:

- 1, Material quality: Dacron yarn
- 2, Working temperature: -50°C to +150°C

- 3, Melting point:  $240^{\circ}\text{C} \pm 10^{\circ}\text{C}$
- 4, Standard color: black
- 5, Certification: ROHS, MSHA, ISO6945
- 6, Cutting tools, scissors or keen knife

## Product drawing



## Product dimension

Part NO.	Lay flat(W) (MM)	ID (MM)	Wall thickness (T)(MM)	Packaging(L)
TLFZ-020	20	10	1.0	50m/roll
TLFZ-025	25	14	1.0	50m/roll
TLFZ-030	30	17	1.0	50m/roll
TLFZ-035	35	20	1.0	50m/roll
TLFZ-040	40	23	1.0	50m/roll
TLFZ-045	45	26	1.0	50m/roll
TLFZ-050	50	29	1.0	50m/roll
TLFZ-060	60	36	1.0	50m/roll
TLFZ-070	70	42	1.0	50m/roll
TLFZ-080	80	48	1.0	50m/roll
TLFZ-090	90	55	1.0	50m/roll
TLFZ-100	100	61	1.0	50m/roll

**Remark:**

- 1, Product size is fold sleeving width ( lay flat width).
- 2, We can provide braided sleeving with special packing and size according to customers' requirement.
- 3, All the dates above are common value, not include customized size.