

FS7015 Size:70*70*15mm DC Axial Fan



Frame:Thermal Plastic,UL 94V-0

Impeller:Thermal Plastic,UL 94V-0

Lead Wire:AWG#24 UL1007(Optional)

(+):Red(-):Black

Insulation Resistance:

Above 10M Between Lead wire and Frame DC500V

Specification:

Model	Bearing	Rated voltage (v)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air flow (CFM)/(m ³ /min)		Air pressure		Noise (dB)	Weight(g)
FS7015H DA12B(S)	sleeve/ball	12	0.35	4.20	4200	33.52	0.94	3.33	0.13	40.0	45
FS7015M DA12B(S)	sleeve/ball	12	0.25	3.00	3600	28.85	0.81	3.02	0.12	35.0	
FS7015L DA12B(S)	sleeve/ball	12	0.16	1.92	3000	24.80	0.69	2.50	0.09	30.0	
FS7015H DA24B(S)	sleeve/ball	24	0.25	6.00	4200	33.52	0.94	3.33	0.13	40.0	
FS7015M DA24B(S)	sleeve/ball	24	0.16	3.84	3600	28.85	0.81	3.02	0.12	35.0	
FS7015L DA24B(S)	sleeve/ball	24	0.12	2.88	3000	24.80	0.69	2.50	0.09	30.0	