

HEBEI JIEBIN WIRE MESH PRODUCTS CO.,LTD.

Nanhuan Economic Development Zone, Anping, China

Tel: +86-318-5281777

Fax: +86-318-5286777

Email: jbwiremesh@vip.126.com

jbwiremesh@gmail.com

Web: www.wiremeshjb.com


www.jiebinwiremesh.com

Razor Wire



1. **Usage:** Residential and commercial security fence, Expressway and highroad barrier fence, Gardens fencing, Boundary fencing, Prison fencing, etc.

2. Type:


● Flat-wrap type

Image	Height (mm)	Length (m)	Weight (Kg/Coil)	Loading quantity (20ft)
	500	15	9.5	900-1000Coils
	700	15	13	700-800Coils
	900	15	14.5	600-700Coils


● Welded type

Image	Mesh type	Mesh size (mm)	Height (m)	Width (m)
	Diamond	75x150	1.2, 1.8, 2.1, 2.4	6
		100x200		
		150x300		
	Square	100x100	1.2, 1.8, 2.1, 2.4	6
		150x150		
		200x200		


● Concertina Coil type

Image	Type	Coil Diameter	No. of Loops	Standard Length per Coil
	BTO-12.18.22.28.30	500mm	102	15M-18M
	BTO-12.18.22.28.30	600mm	86	13M-16M
	BTO-12.18.22.28.30	700mm	72	12M-15M
	BTO-12.18.22.28.30	800mm	64	13M-15M
	BTO-12.18.22.28.30	960mm	52	12M-15M

● **Single Coil Type**

Image	Type	Coil Diameter	No. of Loops	Standard Length per Coil
	CBT-65	450mm	33	7M-8M
	CBT-65	500mm	41	10M
	CBT-65	700mm	41	10M
	CBT-65	960mm	54	11M-15M

3. The common specification of Razor Wire:

Image	Reference Number	Thickness (mm)	Wire Diameter	Blade Length	Blade Width	Blade Spacing
	BTO-10	0.5	2.5mm	10mm	13mm	26mm
	BTO-11	0.5	2.5mm	11mm	13mm	26mm
	BTO-12	0.5	2.5mm	12mm	15mm	26mm
	BTO-22	0.5	2.5mm	22mm	15mm	34mm
	BTO-28	0.5	2.5mm	28mm	15mm	34mm
	BTO-30	0.5	2.5mm	30mm	18mm	34mm
	CBT-60	0.5	2.5mm	60mm	32mm	96mm
	CBT-65	0.5	2.5mm	65mm	21mm	105mm

4. Material:

7101- Hot-dip galvanized steel sheet + hot-dip galvanized wire

7102- Hot-dip galvanized steel sheet + electro galvanized wire

7201- Stainless steel sheet + stainless steel wire

7301- PVC coated galvanized steel sheet + galvanized wire

7401-Zinc/Aluminum coated steel sheet + steel wire