



SPECIFICATIONS

Current Rating : 7A

Insulation Resistance : $\geq 1000 \text{ M}\Omega$

Dielectric Withstanding Voltage :

1200VAC MIN 1Minute

Operating temperature : $-55^\circ \text{C} \sim 105^\circ \text{C}$

Contact Resistance : $\leq 35 \text{m}\Omega$

Insulator Material : PBT & G/F UL 94V-0

Contact Material : Phosphor Bronze

Ordering Code:

V. 35R - F - 34 - X - X - X - X - 01

① ② ③ ④ ⑤ ⑥ ⑦

① CONTACT TYPE:
F:FEMALE
M:MALE

② NO. OF CONTACT:
34:34PIN

③ CONTACT PLATING:
A: GOLD FLASH
S: SELECTIVE GOLD PLATED 3U"
SA: SELECTIVE GOLD PLATED 5U"
SB: SELECTIVE GOLD PLATED 10U"
SC: SELECTIVE GOLD PLATED 15U"
SD: SELECTIVE GOLD PLATED 30U"

④ INSULATOR COLOR:
B:BLUE
K:BLACK

⑤ SHELL:
A:NICKEL PLATED
B:TIN PLATED
C:PORNT NICKEL PLATED
AFTER TIN PLATED

⑥ CONTACT LENGTH:
A:2.6 B:2.7 C:2.8
D:3.0 E:3.2 F:4.75 O:N/A

⑦ SERIES NUMBER:01

Unless Otherwise specified tolerance
X. ±0.35 X.XX: ±0.20
X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
DRAW Wu Feng Rong DATE 03/01/2021
CHECK BobYang DATE 03/01/2021

3rd ANGLE PROJECTION

ANTENK ELECTRONICS CO., LTD
Http://www.antenk.com
E-mail:sales@antenk.com

TITLE:
V. 35 RIGHT ANGLE DIP 34PIN FEMALE CONNECTOR

DRAWING NO: V. 35R-F34XXXX01

PRODUCT NO: V. 35R-F34XXXX01

REV	DESCRIPTION	DATE