

NOTES:

1. MATERIAL: ANNEALED SPRING STEEL, T=0.25mm.
2. PLATING:
80U" Min TIN PLATED OVERALL
50U" Min NICKEL PLATED UNDER OVERALL
3. THIS PRODUCT IS SUITABLE FOR AAA BATTERY CLIP

Order Code:

BS - M - SN - X - 56
 ① ② ③ ④ ⑤

① BS: Battery Contacts

② Apperance For The Product

M: SMT TYPE

④ Packing Method

A: Tray Packing

R: Tape & Reel Packing

B: Bag Packing

③ Contact Plating

SI: NICKEL PLATE

SN: Tin

G0: Gold Flash

G1: 3u" Gold

G2: 5u" Gold



G3: 10u" Gold

G4: 15u" Gold

G5: 30u" Gold


⑤ Product Number

56:56 STYLE



Unless Otherwise specified tolerance
 X. ± 0.50 X. XX: ± 0.25
 X. X: ± 0.35 X. XXX: ± 0.10

SCALE: As Shown UNIT: mm
 DRAW Wu Feng Rong DATE 28/08/2020
 CHECK BobYang DATE 28/08/2020



ANTENK ELECTRONICS CO., LTD
[Http://www.antenk.com](http://www.antenk.com)
 E-mail: sales@antenk.com

△ Change Dimensions refer to keystone

09/15/2022

△ Change R to M

06/04/2022

⚠ Update Product Number

08/07/2021

REV

DESCRIPTION



DATE

TITLE:
Battery Holder 56 STYLE FOR AAA BATTERY

DRAWING NO: BS-M-SN-X-56

PRODUCT NO: BS-M-SN-X-56

HSF



NOTES:

TAPE AND REEL SPECIFICATIONS:

1. TAPE:

MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANS/EIA-481 STANDARD

1.260 [32.0] WIDE; .787 [20.0] PITCH

2. REEL:

13.0 [330.2] DIA. 250 PIECES PER REEL.

.500 [12.7] MIN.
DIA. HOLE
THRU

±.005 [±0.13]
.157 [4.0]

±.005
[±0.13]

PITCH

±.005 [±0.13]
.059 [1.5] DIA.
HOLE (TYP.)

.079 [2.0]

.431 [10.95]
REF.

±.005
[±0.13]
WIDTH

.551 [14.0]
REF.

Unless Otherwise specified tolerance
X.±0.35 X.XX:±0.20
X.X:±0.25 X.XXX:±0.15

SCALE: As Shown UNIT: mm
DRAW ZLA DATE 12/08/2022
CHECK BobYang DATE 12/08/2022

VER./版本号
3rd ANGLE PROJECTION

Antenk® ANTENK ELECTRONICS CO.,LTD
Http://www.antenk.com
E-mail:sales@antenk.com

TITLE: Battery Holder 56 STYLE FOR AAA BATTERY

DRAWING NO: BS-M-SN-X-56

PRODUCT NO: BS-M-SN-X-56

MK/标记

DESCRIPTION/修订内容

DATE/日期(M/D/Y)