

NOTE:

1. ALL INSIDE BEND RADII TO BE A MIN. OF MATERIAL THICKNESS UNLESS OTHERWISE SPECIFIED.
2. PART MUST BE FREE OF ALL BURRS AND SHARP EDGES.

3. MAT'L: 0.254 TH'K FULL HARD PHOSPHOR BRONZE
4. FINISH: NICKEL PLATE
0.00254-0.00762 NICKEL, OVER
0.00127-0.00254 COPPER
5. INDICATES CRITICAL DIMENSION

NOTES:

1. MATERIAL:
0.30mm PHOSPHOR BRONZE, NICKEL PLTD.
2. ROHS 2 COMPLIANT

BS - S - SI - R - CR2032R
① ② ③ ④ ⑤

① BS: Battery Contacts


② Apperance for the product
S:180 TYPE

③ Contact Plating
SI: Nickel Plate
SN: Tin
G0: Gold flash
G1: 3U" Gold
G2: 5U" Gold
G3: 10U" Gold
G4: 15U" Gold
G5: 30U" Gold

④ Packing method
A: Tray packing
R: Tape & reel packing
⑤ Product number
CR2032R

Unless Otherwise specified tolerance
X. ±0.35 X.XX: ±0.20
X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown	UNIT: mm
DRAW Lv Xun Hua	DATE 02/07/2019
CHECK BobYang	DATE 02/07/2019



Antenk® ANTENK ELECTRONICS CO.,LTD
Http://www.antenk.com
E-mail:sales@antenk.com

TITLE: BATTERY CONTACTS FOR CR2032

DRAWING NO: BS-S-SI-R-CR2032R

PRODUCT NO: BS-S-SI-R-CR2032R

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		