

MOUNTING LAYOUT 装配图
TOLERANCE ±0.05 UNLESS OTHERWISE SPECIFIED.
默认公差±0.05

NOTES/说明:

- 1. BASE 胶芯:
MAT'L材料- PBT (UL94V-0) BLACK 黑色
- CONTACTS端子:
MAT'L材料 - 0.25 Th'K SPRING STEEL/0.25mm 厚 弹簧钢
HEAT TREAT TO SPRING TEMPER. 高温热处理


Order code 订单编号:

BT - S - SN - B - CR1632A-069
① ② ③ ④ ⑤

- ① BT: Coin Cell Holders 纽扣电池
- ② Apperance for the product 连接形式
S:180 TYPE
- ③ Contact Plating 端子电镀
SN:Tin/锡
G0:Gold flash /普金
G1: 3U" Gold/金
G2: 5U" Gold/金
G3:10U" Gold/金
G4:15U" Gold/金
G5:30U" Gold/金
- ④ Packing method 包装方式
A: Tray/吸塑盒装 B:Bag/袋装
R: Tape & reel/卷装
- ⑤ Product number /产品编号
CR1632A-069

Unless Otherwise specified tolerance
X. ±0.35 X.XX:±0.20
X.X:±0.25 X.XXX:±0.15

SCALE: As Shown UNIT: mm
DRAW ZLA DATE 24/05/2022
CHECK BobYang DATE 24/05/2022



Antenk® ANTENK ELECTRONICS CO.,LTD
Http://www.antenk.com
E-mail:sales@antenk.com

TITLE: COIN CELL HOLDER FOR BR1612, CR1616, CL1620, CR1625, BR1632 DIP 180°

DRAWING NO: BT-S-SN-B-CR1632A-069

PRODUCT NO: BT-S-SN-B-CR1632A-069

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		