



SHELL:	STEEL
FINISH:	
SHELL:	NICKEL

<u>PDB13W3</u>	<u>-M</u>	<u>-G0</u>	<u>-B</u>	<u>-20</u>
(1)	(2)	(3)	(4)	(5)

- ① Series
- ② Contact Type:
M:Male F:Female
- ③ Contact NO.:
G0: Gold flash G1: 3u" Gold
G2: 5u" Gold G3: 10u" Gold
G4: 15u" Gold G5: 30u" Gold
- ④ Insulation Color Code:
B:Black L:Blue
W:White
- ⑤ Power AMP:
10 = 10AMPS; 20 = 20AMPS;
30 = 30AMPS; 40 = 40AMPS;

Unless Otherwise specified tolerance	
X. ± 0.35	X.XX: ± 0.20
X.X: ± 0.25	X.XXX: ± 0.15

SCALE: As Shown	UNIT: mm
DRAW Lv Xun Hua	DATE 27/05/2019
CHECK BobYang	DATE 27/05/2019



Antenk® ANTENK ELECTRONICS CO.,LTD
Http://www.antenk.com
E-mail:sales@antenk.com

POWER D-SUB 13W3 SOLDER CUP-MALE

PRODUCT NO:	PDB13W3-MXXX
-------------	--------------

REV	DESCRIPTION