



CKT. SIZE	A	B	C
10	16.65	8.00	11.65
12	18.65	10.00	13.65
14	20.65	12.00	15.65
16	22.65	14.00	17.65
20	26.65	18.00	21.65
22	28.65	20.00	23.65
26	32.65	24.00	27.65
34	40.65	32.00	35.65
40	46.65	38.00	41.65
44	50.65	42.00	45.65
50	56.65	48.00	51.65

SPECIFICATION

Current Rating: 1.0Amp
 Insulation Resistance: 1000MΩ min
 Contact Resistance: 20MΩ max
 Withstand Voltage: 500V AC/DC
 Operating Temperature: -40° C to +105° C
 Contact Material: Phosphor Bronze
 Contact Plating: Au Over Ni
 Insulator Material: PBT+30%GF UL 94V-0

Ordering Code:

FCCS06 - X - X - X - X - X
 ① ② ③ ④ ⑤ ⑥

- ① Series No:
- ② No. of Contacts
06P 08P 10P
12P 14P 16P
18P 20P 22P
24P 26P 30P
34P 36P 40P
44P 50P 60P
64P
- ③ Contact Plating
G0: Gold flash S0: Gold flash/Ni
G1: 3u" Gold S1: 3u" Gold/Ni
G2: 5u" Gold S2: 5u" Gold/Ni
G3: 10u" Gold S3: 10u" Gold/Ni
G4: 15u" Gold S4: 15u" Gold/Ni
G5: 30u" Gold S5: 30u" Gold/Ni
SN: Tin
- ④ Color Insulator
B:Black
G:Grey
- ⑤ Packing
A:Tray
B:Bag
C:Tube
D:Tape Reel
- ⑥ With Strain relief or not
A: With strain relief
B: without strain relief

Unless Otherwise specified tolerance
 L I: ±0.35 L II: ±0.20
 L X: ±0.25 L III: ±0.15

SCALE: As Shown UNIT: mm

DRAW Gong Feng DATE 08/03/2017
 CHECK BobYang DATE 08/03/2017



Antenk ANTEK ELECTRONICS CO., LTD
 Http://www.antenk.com
 E-mail:sales@antenk.com

TITLE:
2.00mm IDC Socket With Latch

DRAWING NO: FCCS06-XXXXX

PRODUCT NO: FCCS06-XXXXX

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		