



SPECIFICATIONS

Current Rating :7A
 Insulation Resistance : $\geq 1000 \text{ M}\Omega$
 Dielectric Withstanding Voatge :
 1200VAC MIN 1Minute
 Operating temperature : $-55^{\circ} \text{C} \sim 105^{\circ} \text{C}$
 Contact Resistance : $\leq 35 \text{m}\Omega$
 Insulator Material :PBT & G/F UL 94V-0
 Contact Material : Phosphor Bronze

Ordering Code:

V. 35R - F - 21 - X - X - X - X - 01
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① CONTACT TYPE:
F:FEMALE
M:MALE
- ② NO. OF CONTACT:
21:21PIN
- ③ CONTACT PLATING:
A: GOLD FLASH
S: SELECTIVE GOLD PLATED 3U"
SA: SELECTIVE GOLD PLATED 5U"
SB: SELECTIVE GOLD PLATED 10U"
SC: SELECTIVE GOLD PLATED 15U"
SD: SELECTIVE GOLD PLATED 30U"
- ④ INSULATOR COLOR:
B:BLUE
K:BLACK
- ⑤ SHELL:
A:NICKEL PLATED
B:TIN PLATED
C:PORNT NICKEL PLATED
APTER TIN PLATED
- ⑥ CONTACT LENGTH:
A:2.6 B:2.7 C:2.8
D:3.0 E:3.2 F:4.75 O:N/A
- ⑦ SERIES NUMBER:01

Unless Otherwise specified tolerance
 X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

Antenk ANTENK ELECTRONICS CO.,LTD
[Http://www.antenk.com](http://www.antenk.com)
 E-mail:sales@antenk.com

SCALE: As Shown	UNIT: mm
DRAW Wu Feng Rong	DATE 03/01/2021
CHECK BobYang	DATE 03/01/2021

TITLE:
V. 35 RIGHT ANGLE DIP 21PIN FEMALE CONNECTOR

DRAWING NO: V. 35R-F21XXXX01
 PRODUCT NO: V. 35R-F21XXXX01



REV	DESCRIPTION	DATE