


Also accepts:AAA
 Material 0.3 Spring stell nickel plated
 Coating parameters:4um
 Temperature range:-40° C - 270° C
 Voltage parameters:270V

Order code:
 BS - S - SI - R - CR125A
 ① ② ③ ④ ⑤

- ① BS: Battery contacts
- ② Apperance for the product
- S:180 TYPE
- ③ Contact Plating
 SI: NICKEL Plated
 SN: Tin
 G0: Gold flash
 G1: 3U" Gold
 G2: 5U" Gold
 G3: 10U" Gold
 G4: 15U" Gold
 G5: 30U" Gold
- ④ Packing method
 A: Tray packing
 R: Tape & reel packing
- ⑤ Product number:
 CR125A

Unless Otherwise specified tolerance
 X. ± 0.35 X. XX: ± 0.20
 X. X: ± 0.25 X. XXX: ± 0.15

SCALE: As Shown UNIT: mm
 DRAW Lv Xun Hua DATE 23/05/2019
 CHECK BobYang DATE 23/05/2019



Antenk ANTENK ELECTRONICS CO.,LTD
[Http://www.antenk.com](http://www.antenk.com)
 E-mail:sales@antenk.com

TITLE: Battery Contacts For CR125A

DRAWING NO: BS-S-SI-R-CR125A

PRODUCT NO: BS-S-SI-R-CR125A

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		