

SP90Y

90-ton lifting capacity

- ▶ Engine model: Cummins QSX15
- ▶ Rated power: 291 kW
- ▶ Operating weight: 58 t

Product features

Delivering ultimate power, lift and value, the SP90Y features a Cummins engine, load feedback, overload prevention, anti-rollover protection and precise controls. Our first offering for larger loads.



SHANTUI

VALUE THAT WORKS

Shantui Construction Machinery Co., Ltd.

ADDRESS:

No. 58, G327 Highway
Jining City, Shandong, CHINA

TEL: +86-537-2909369

FAX: +86-537-2311219

EMAIL: trade@shantui.com


SP90Y

Technical specifications:

SP90Y

	WEIGHT AND DIMENSIONS	Operating weight	58000 kg
		Maximum lifting weight	92600 kg
		Track shoe width	860 mm
		Minimum turning radius	3950 mm
		Ground length	3620 mm
		Ground clearance	550 mm
	SERVICE REFILL CAPACITIES	Fuel tank capacity	600 L
		Hydraulic tank capacity	315 L
		Engine oil	45 L
		Cooling system	121 L
	ENGINE	Rated power	291 kW
		Model	Cummins QSX15
		Piston displacement	15 L
		Stroke-bore × stroke	6-137 × 169 mm
		Rated revolution	2000 rpm
	TRANSMISSION SYSTEM	Type	Hydraulic transmission
		Hydraulic torque converter	3-element, 1 stage, 1 phase
		Transmission	Planetary gear, forced lubrication
		Number of track rollers (each side)	9
		Number of carriers (each side)	2
		Travel speed 1st (forward/reverse)	3.6/4.4 km/h
		Travel speed 2nd (forward/reverse)	6.6/7.8 km/h
	WORKING PUMP	Type	Duplex pump
		Displacement of large pump	130 ml/r
		Displacement of small pump	-
		Rated working pressure	11 MPa
	PIPELAYING EQUIPMENT	Boom Length	8600 mm
		Max. lifting height	7000 mm
		Boom swing amplitude	1200~8900 mm
		Boom Line speed	6 m/min
		Gradeability	20°
		Ground press	0.091 MPa

OVERALL DIMENSIONS



▶ THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.

WWW.SHANTUI.COM