

## Features

- Industrial standard package
- Electrically insulated base plate
- Heat transfer through aluminium oxide ceramic insulated metal base plate
- Chip soldered on direct copper bonded  $AL_2O_3$  ceramic
- Thyristor chip with center gate

## Typical Applications

- DC motor control
- AC motor soft starters
- Temperature control
- Professional light dimming

$V_{DRM}/V_{RRM}$		1600/1600	V
$V_{RSM}$		1700	V

## Maximum Ratings

Symbol	Condition	Ratings	Unit
$I_{T(AV)}$	sin. 180; $T_c = 85^\circ C$ ,	95	A
$I_{TSM}$	$T_{vj} = 25^\circ C$ ; 10 ms	2000	A
$I^2t$	$T_{vj} = 25^\circ C$ ; 8,3...10 ms	20	$kA^2S$
$(di/dt)_{cr}$		140	A/us
$V_{iso}$	A.C. 1s / 1min.	3600/3000	V
$T_j$		-40 ~ + 125	$^\circ C$
$T_{stg}$		-40 ~ + 125	$^\circ C$
W		-	g

## Electrical Characteristics

Symbol	Condition	Ratings	Unit
$I_{DRM} / I_{RRM}$	At $V_{DRM}$ , $T_j = 125^\circ C$	15	mA
$V_T$	On-State Current 300A, $T_j = 25^\circ C$	1.63	V
$V_{T(TO)}$	$T_j = 125^\circ C$	0.9	V
$t_{gd}$	$T_j = 25^\circ C$	1	us
$t_q$	$T_j = 125^\circ C$	100	us
$I_{GT}/V_{GT}$	$T_j = 25^\circ C$	150 / 3	mA/V
$V_{GD}$	$T_j = 125^\circ C$	0.25	V
$(dv/dt)_{cr}$	$T_j = 125^\circ C$	1000	V/us
$I_H$	$T_j = 25^\circ C$ , typ. / max.	140/240	mA
$I_L$	$T_j = 25^\circ C$ , typ. / max.	260/550	mA
$R_{th(j-c)}$	Per Module	0.14	K/W

