

MBXS SERIES

YZPST[®]

MINIATURE SINGLE-PHASE SURFACE MOUNT BRIDGE RECTIFIER

产

品

规

确

格

认

书

MB05S THRU MB10S

YZPST.[®]

MINIATURE GLASS PASSIVATED SINGLE-PHASE SURFACE MOUNT BRIDGE RECTIFIER


REVERSE VOLTAGE: 50 to 1000 VOLTS

FORWARD CURRENT: 0.5 AMPERE

FEATURES

- Glass passivated chip junction
- Low forward voltage drop
- High surge overload rating of 30 Amperes peak
- Ideal for printed circuit board
- High temperature soldering guaranteed:
260°C for 10 seconds

MD-S



MECHANICAL DATA

Case: Molded plastic, MD-S

Epoxy: UL 94V-O rate flame retardant

Terminals: Leads solderable per MIL-STD-202,
method 208 guaranteed

Mounting position: Any

Weight: 0.008ounce, 0.22gram

Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25° ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	Symbols	MB05S	MB1S	MB2S	MB4S	MB6S	MB8S	MB10S	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current (see Fig. 1) on glass-epoxy P.C.B (Note 2) on aluminum substrate (Note 3)	I _(AV)				0.5				Amp
					0.8				
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I _{FSM}				30				Amp
Maximum Forward Voltage at 0.4A DC and 25°	V _F				1.0				Volts
Maximum Reverse Current at T_A=25° at Rated DC Blocking Voltage T_A=125°	I _R				5.0				uAmp
					500				
Typical Junction Capacitance (Note 1)	C _J				13				pF
Typical Thermal Resistance (Note 3)	R _{0JA}				70				/W
Typical Thermal Resistance (Note 2)	R _{0JL}				20				/W
Operating and Storage Temperature Range	T _J , T _{stg}				-55 to +150				

NOTES:

1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

2- On glass epoxy P.C.B. mounted on 0.05 x 0.05" (1.3 x 1.3mm) pads

3- On aluminum substrate P.C.B. with an area of 0.8" x 0.8" (20 x 20mm) mounted on 0.05 x 0.05" (1.3 x 1.3mm) solder pad

RATINGS AND CHARACTERISTIC CURVES

Fig. 1 - Derating Curve for Output Rectified Current




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current Per Leg




Fig. 3 - Typical Forward Voltage Characteristics Per Leg




Fig. 4 - Typical Reverse Leakage Characteristics Per Leg




Fig. 5 - Typical Junction Capacitance Per Leg

