

Specifications

Model No.	YAPS06A
AC Input	
Nominal Input Voltage	AC 100V~240V
Input Voltage Range	AC 95V~265V
Input Frequency	50/60Hz
DC Output	
Output Voltage	14.5V
Output Current	2A
Output Power	29W
DC Connector	type-C USB
Line Regulation	2%
Load Regulation	5%
Ripple Noise	180 Mvp-p
Efficiency	>85%
Output Cable Standard	0.5mm ² Pure Copper
Output Cable Length	1m and 1.8m type-c cable for choose
Environment	
Operating Temperature	0°C ~40°C
Operating Humidity	5%~95%RH
Storage Temperature	-20°C ~85°C
Storage Humidity	5%~95%RH
Protection	
Over Load Protection	Short Circuit Protection
Over Current Protection	Over Temperature Protection
Certificates	
CE, ROHS, REACH, FCC, ERP, CB, GS, TUV, UL, CUL, CCC,PSE	
Dimensions	
Adapter Size	5*3*5CM
Adapter Weight	90G
Color Box Size	6.5*3.2*8CM
Color Box Weight	19.5G
Brown box size	19*13*4.7CM
Brown box weight	40G
PCS/CTN	50PCS
Outer Carton Size	48.5*32*40CM
Outer Carton Weight	860G

GW/CTN	14500G
Spare parts	
type-c adapter, EU/US/UK/AUS plugs for choose, 1m and 1.8m type-c cable for choose	
Package	
Inner Box	each adapter is in a neutral color box, then into a brown box with plug and type-c cable
Outer Carton	Normally neutral standard carton or customized requirement
Warranty	
Guarantee	30 days
Warranty	2 years
Terms and Conditions	
MOQ	100PCS for mixed order
Payment Terms	T/T, L/C, western union
Delivery Time	3-5 days
Manufacturing Process	
1. Set-Up→2. Hand Insertion→3. Wave Soldering→4. Touch-Up→5. V/I→6. ICT→7. INT→8. Apply Glue→9. Q/A→10. Entering Stock→11. Assembly→12. Power On Test→13. Hi-Pot Test→14. Burn-In→15. Hi-Pot Test→16. All Fun Test→17. Packing→18. OQC→19. Shipping	
Test Procedures	
1.No-load output voltage test→2.input power load test→3.No-load output ripple test→4.Full load open test→5.Full load output voltage test→6.Full load output ripple test→7.Full load input power test→8.Half load output voltage test→9.Half load output ripple test→10.Over load test→11.Over current protection test →12.Short circuit protection test (above test is under both 110V and 230V.)→13.High voltage test→14.burn-in test→15.Turn on delay time test→16.Rise time test→17.Hold time test→18.Overshoot test	