

# LED Shoebox Light BRIGHTEN YOUR LIFE

NEW LED TECHNOLOGY THAT ALLOWS THE COEXISTENCE OF ENVIRONMENTAL PROTECTION AND ENERGY SAVING

# **Benefits**

- 1. Replace conventional Shoebox Lights
- 2. Precision Die Cast Aluminum Housing
- 3. Fade Resistant Powder Coat Finish
- 4. Easy Installation
- 5. CE ROHS listed





CE ROHS



#### **Features**

- 1. Beam angle:60 90 120 degrees.
- 2. Aluminum die-casting heat sinks is good for heat dissipation.
- 3. It's major to replace the conventiona highbay light.
- 4. Green, energy saving, long and reliable life of 50,000 hours.
- 5. No RF interference, No IR/UV radiation , no mercury pollution.
- 6. Wide colour availability in degrees Kelvin(K),2700-6700K.
- 7. Streamline exterior design, beautiful appearance.
- 8. Environment friendly ,energy saving (70~80%).
- 9. Special circuit design, each LED work separately, avoiding the single broken LED influence problem.



#### Application


- 1.Stadium Lighting.
- 2.Parking lot lighting.
- 3.Industrial Lighting.
- 4. Port wharf Lighting.
- 5.Roadway Lighting.





## **SPECIFICATIONS**

| Power             | 300W   | 500W             | 600W          | 800W          | 1000W          | 1200W          |  |  |  |
|-------------------|--|------------------|---------------|---------------|----------------|----------------|--|--|--|
| Model             | BB-LD-300W-CQ  | BB-LD-500W-CQ    | BB-LD-600W-CQ | BB-LD-800W-CQ | BB-LD-1000W-CQ | BB-LD-1200W-CQ |  |  |  |
| Luminous Flux     | 39000lm  | 65000lm          | 78000lm       | 104000lm      | 130000lm       | 1560000lm      |  |  |  |
| Replacement       | HPS 1000W  | HPS 1500W        | HPS 2000W     | HPS 2500W     | HPS 3000W      | HPS 3500W      |  |  |  |
| Beam Angle        | 60° 90° 120°   | 120° 15° 30° 60° |               |               | 15° 30°        |                |  |  |  |
| Dimension         | 463*400*220mm  | m 652*562*352mm  |               |               | Coming soon    |                |  |  |  |
| Luminous Efficacy | SMDLED   |                  |               |               |                |                |  |  |  |
| Luminous Efficacy | 130lm/W  |                  |               |               |                |                |  |  |  |
| Operation Temp.   | -40 to +45°C   |                  |               |               |                |                |  |  |  |
| ССТ               | 2700K SW / 3000K WW / 4100K NW / 5000K DW / 5700K CW                                 |                  |               |               |                |                |  |  |  |
| CRI               | 85   |                  |               |               |                |                |  |  |  |
| Life Span         | 50,000 hours at 25℃  |                  |               |               |                |                |  |  |  |
| Voltage           | 100-277VAC/50-60HZ   |                  |               |               |                |                |  |  |  |
| Driver            | UL listed power supply   |                  |               |               |                |                |  |  |  |
| Dimming           | Available  |                  |               |               |                |                |  |  |  |
| Sensor            | Microwave sensor Daily sensor available  |                  |               |               |                |                |  |  |  |
| Control System    | APP, remote control, touch screen, light control and other control options available |                  |               |               |                |                |  |  |  |
| Cover             | Transparent, Matte, Lens available   |                  |               |               |                |                |  |  |  |
| IP                | 65   |                  |               |               |                |                |  |  |  |
| PF                | >0.95  |                  |               |               |                |                |  |  |  |
| Warranty          | 5Years   |                  |               |               |                |                |  |  |  |

#### DIMENSIONAL DRAWING








500W-800W

### LUMINOUS INTENSITY DISTRIBUTION



#### PROJECTS

By using our 500W Highbay Light to replace 1500W Metal Halide bulb for shoebox lighting fixtures, the customer is now able to save a lot per month from his electric bill.



#### 500W LED = 1500W MH

#### Note:

- Don't take the LED lamp apart.
- The LED lamp must work under the right voltage according to the specification.

# PACKING INFO

| ENERGY SAVING<br>tradite<br>DISH PACK |  | Packaging    | Carton Size(mm)<br>(L*W*H) | N.W    | G.W    | Volume weight |
|---------------------------------------|--|--------------|----------------------------|--------|--------|---------------|
|                                       |  | 300W/1pc     | 425*425*220mm              | 13.6kg | 14.6kg | 10.0kg        |
|                                       |  | 500-800W/1pc | 600*600*300mm              | 15.5kg | 15.5kg | 25.0kg        |