

Smart-UPS

APC Smart-UPS 3000VA USB & Serial 230V

APC Smart-UPS, 2700 Watts / 3000 VA, Input 230V / Output 230V, Interface Port DB-9 RS-232, SmartSlot, USB

Includes: CD with software, Smart UPS signalling RS-232 cable, USB cable, User Manual

Output

Output Power Capacity

2700 Watts / 3000 VA

Max Configurable Power

2700 Watts / 3000 VA

Nominal Output Voltage

230V

Output Voltage Note

Configurable for 220 : 230 or 240 nominal output voltage

Efficiency at Full Load

95.0%

Output Voltage Distortion

Less than 5% at full load

Output Frequency (sync to mains)

47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal

Topology

Line Interactive

Waveform Type

Sine wave

Output Connections

(8) IEC 320 C13

(1) IEC 320 C19



(2) IEC Jumpers

Input

Nominal Input Voltage

230V

Input Frequency

50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

IEC-320 C20

Schuko CEE 7 / EU1-16P

British BS1363A

Input voltage range for main operations

160 - 285V

Input voltage adjustable range for mains operation

151 - 302V

Batteries & Runtime

Battery Type

Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof

Typical recharge time

3 hour(s)

Replacement Battery

[RBC55](#)

RBC™ Quantity

1

Communications & Management

Interface Port(s)

DB-9 RS-232, SmartSlot, USB

Available SmartSlot™ Interface Quantity

1

Control panel

LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators

Audible Alarm

Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO)

Yes

Surge Protection and Filtering

Surge energy rating

320 Joules

Filtering

Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height

432.00 mm

Maximum Width

196.00 mm

Maximum Depth

544.00 mm

Net Weight

55.91 KG

Shipping Weight

64.55 KG

Shipping Height

559.00 mm

Shipping Width

381.00 mm

Shipping Depth

762.00 mm

Color

Black

Units per Pallet

3.00

Environmental

Operating Environment

0 - 40 °C

Operating Relative Humidity

0 - 95%

Operating Elevation

0-3000 meters

Storage Temperature

-15 - 45 °C

Storage Relative Humidity

0 - 95%

Storage Elevation

0-15000 meters

Audible noise at 1 meter from surface of unit

53.00 dBA

Online Thermal Dissipation

375.00 BTU/hr