



ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

**Chorus**

Email: sales@cn-lubricantadditive.com; Web: www.cn-lubricantadditive.com

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, 13783582233

---

### Antiwear EP Additive Tricresyl Phosphate TCP T306

#### ●Product Introduction

Antiwear EP Additive Tricresyl Phosphate TCP T306 is a transparent oily liquid. It has excellent anti-extreme pressure, antiwear, fire inhibition properties. It has few unpleasant odor.

#### ●Application

It is used primarily for blending gear oil and antiwear hydraulic oil. It can also be used for fire inhibition hydraulic oil.

#### ●Recommended Dosage:

The recommended dosage is from 0.5wt% to 1.5wt%.

#### ●Product Quality Characteristics & Test Method

| Item                              | Typical Value                      | Test Method       |
|-----------------------------------|------------------------------------|-------------------|
| Appearance                        | Light yellow<br>transparent liquid | Visual Inspection |
| Density (20°C), kg/m <sup>3</sup> | ≤1190                              | GB/T1884          |
| Flash Point (COC), °C             | ≥220                               | GB/T267           |
| Acid Number, mgKOH/g              | ≤0.25                              | SH/T264           |
| Free Phenol Content, wt%          | ≤0.20                              | Q/SY206009        |

#### ●Storage and Transportation

It is packed in 200L metal drums or according to user requirements packaging.

The storage, transportation and production should meet the requirements of SH/T0164.

The maximum temperature should not exceed 75°C, for long term storage, the maximum temperature should not exceed 45°C.

The product is toxic. Please pay attention to the safety protection.