



ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

Email: eilin@cn-lubricantadditive.com; Web: www.cn-lubricantadditive.com

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, 18339818406

GL5 GL4 Gear Lubricant Oil Additive Package

●Product Introduction

T4206 have excellent high-temp antioxidant, anti-corrosion, antifoaming, demulsibility. It can prolong the service life of gear teeth and bearing, lower filter blocking. This product is suitable for blending gear oils that conform to the API GL-4, GL-5. Contains no metallic elements, soluble in I, II base oils and PAO.

●Recommended Dosage:

API Performance Level	Treating Rate (mass%)
GL-5	4.2%
GL-4	2.1%
High Load-carrying	1.6%
Low, Mid Load-carring	1.2%

●Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Appearance	Yellow Liquid	Visual
Kinematic Viscosity (100°C), mm ² /s	Report	ASTM D445
Sulphur, wt%	31	ASTM D5185
Phosphorus, wt%	1.69	ASTM D5185

●Product Storage/Handling/Transportation/Package

It is packed 200KG in each drum.

The storage, transport and production should meet the requirement of SH/T0164.

The maximum temperature should not exceed 75°C, for long-term storage, the maximum temperature should not exceed 45°C. The product is not flammable, explosive, and corrosive. Its safety cause, environmental protection and usage may refer the general procedures for the common petroleum products.