



ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

Email: [eilin@cn-lubricantadditive.com](mailto:eilin@cn-lubricantadditive.com); Web: [www.cn-lubricantadditive.com](http://www.cn-lubricantadditive.com)

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, +86-18339818406

---

## Multifunctional Air Compressor Lube Oil Additive Package

### ●Contact Information:

Sales Manager: Eilin

Email:[eilin@cn-lubricantadditive.com](mailto:eilin@cn-lubricantadditive.com)

Whatsapp/Line: +8618339818406

### Product Introduction

T66063 is formulated with different kinds of Antiwear EP Additive, High Temperature Antioxidant, Rust Preventative Anti-rust Additive, etc. It has excellent anti-wear, high-temp anti-oxidation and antirust properties. It can also inhibits the formation of carbon sludge and has outstanding demulsibility. The oil blended with T66063 can meet the standard of foreign similar products.

### Recommended Treat Rate (wt%):

L-DAA: 0.30-0.60%

L-DAB: 0.60-0.80%

L-DAG: 1.15%

Net Weight: 170 Kgs/Drum

Storage and Transportation:Non-dangerous goods, store in dry, cool ventilated area.

### Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Appearance	Yellow transparent liquid	Visual
Kinematic Viscosity, 100°C, mm <sup>2</sup> /s	Report	ASTMD445
Flash Point, °C	> 110	ASTMD92