



Lubricant Oil Anti-foam Additive Package

●Product Introduction

Defoamer is an additive to eliminate foam. In the fields of coating, textile, medicine, fermentation, papermaking, water treatment and petrochemical industry, a large amount of foam will be produced, which will affect the quality and production process of products. Based on the inhibition and elimination of foam, it is usually necessary to add special defoamer in production.

This product adopts patented technology, it has a little effect on air release, and have effective anti-foaming ability for special foaming substances. This kind of additive have good oil solubility, easy to use, no need to dilute, and can added to oil products directly.

●Recommended Treat Rate

Oil blending type	Recommended dosage g/MT
Hydraulic oil	70
Gear oil	100
Internal combustion engine oil	60
Other industrial oil	50~100

●Technical data

Analysis item	Technical index	Check the data	Test method
appearance	Transparent liquid	Transparent liquid	Visual inspection
Density (20 °C) kg / M ³	Report	0.81	GB/T1884
Kinematic viscosity(40°C), mm ² /s _≥	Actual	4	GB/T265
Flash point (opening), °C _≥	Actual	85	GB/T3536
Aromatics content	Actual	0.18	SH/T0689

●Package, Storage and Transportation

This kind of product is non-flammable, non-explosive and non-corrosive. Packaging, labeling, transportation, storage and acceptance of delivery should carry out by SH0164 Product packaging: 150kg metal drum or according to user requirements packaging.

Remarks: If it touches the skin carelessly, you can wash through detergent and water.