



ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

Email: sales@cn-lubricantadditive.com; Web: www.cn-lubricantadditive.com

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, 13783582233

CI-4 Plus Diesel Engine Oil Additive Package T6072

●Product Introduction

This product T6072 is a diesel engine oil package that blend by various kinds of TBN Booster Calcium Sulfonate, Ashless Dispersant, Corrosion Inhibitor ZDDP, High Temperature Antioxidant and other Lubricant Additive Component. It has excellent dispersion of soot, high temperature detergency, oxidation resistance and corrosion resistance. And this product on the basis of T6071, use the most advanced high molecular weight ash free dispersant, which endows the product with excellent dispersity in high soot content.

●Recommended Dosage

API Performance Level	Treating Rate (mass%)
CI-4 plus	13.4%

●Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Appearance	Brown viscous liquid	Visual Inspection
Density(20°C) , kg/m ³	982	GB/T13377, ASTMD4052
Kinematic Viscosity (100°C) , mm ² /s	250	GB/T265, ASTMD445
Flash Point (COC), °C	<180	GB/T3536, ASTMD92
Total Base Number, mgKOH/g	85	SH/T0251, ASTMD2896
Zn Content, %(m/m)	1.3	GB/T17476, ASTM D4951
Ca Content, %(m/m)	2.3	GB/T17476, ASTM D4951
P Content, %(m/m)	1.2	GB/T17476, ASTM D4951

●Product Storage/Handling/Transportation/Package

The product is packed with 200 litre iron drum or according to user`s requirement. Specific weight of delivery is subject to the actual filling weight. The storage temperature should not exceed 50°C, the loading/unloading and blending temperature should not exceed 60°C.