

ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

horus Email: eilin@cn-lubricantadditive.com; Web: www.cn-lubricantadditive.com Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, 18339818406

Two-stroke Motor Engine Oil Additive Package T3303

•Contact Information:

Sales Manager: Eilin

Email:eilin@cn-lubricantadditive.com

Whatsapp/Line: +8618339818406

• Product Introduction

The product is formulated with low base number detergent and dispersant. It has excellent detergency, lubricative and dispersancy. This product is suitable for blending FB and FC level air cooling two-stroke motor engine oils that conform to the standard JASO M345 FB and FC.

• Characteristics

Typical Value	Test Method
Report	ASTMD445
>110	ASTMD92
≥0.5	ASTMD5185
≥0.7	ASTMD5762

•Recommended Dosage

API FB 4.0wt%; API FC 5.7wt%

Product Storage/Handling/Transportation/Package

The storage temperature should not exceed 50°C, the loading/unloading and blending temperature should not exceed 60°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection, use, etc. It is same as normal petroleum product, with no special protection. Product package: Net Weight: 200 Kgs/Drum