



ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

Email: [eilin@cn-lubricantadditive.com](mailto:eilin@cn-lubricantadditive.com); Web: [www.cn-lubricantadditive.com](http://www.cn-lubricantadditive.com)

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, +86-18339818406

---

## Ashless Anti-wear Hydraulic Lube Oil Additive Package

### 1. Product Introduction

The Ashless Hydraulic Oil Additive Package T5038 is formulated with selected anti-wear agent and ashless antioxidant, etc. It has excellent anti-wear, anti-oxidation abilities and demulsibility. Unique ashless anti-wear formula can effectively protect the silver-containing parts and prolong the service life of the pump.

### 2. Recommended Dosage:

Performance Level	Dosage(W%)
HM Ashless	0.68-0.8%

### 3. Characteristics

Item	Typical Value	Test Method
Appearance	Yellow transparent liquid	Visual
Kinematics Viscosity (100°C) mm <sup>2</sup> /S	Report	ASTMD445
Flash Point, °C	> 110	ASTMD92
Sulphur,wt%	> 2.4	ASTMD5185
Phosphorus, wt%	> 25	ASTMD5185

### 4. Package And Storage

It is packed 200Kg in each drum.

The storage, transport and production should meet the requirements of SH/T0164. The maximum temperature should not exceed 75°C, for long-term storage, the maximum temperature should not exceed 45°C. The product is not flammable, explosive, and corrosive. Its safety cause, environmental protection and usage may refer to the general procedures for the common petroleum products.